



| | |
|-------------|--|
| DATE | |
| PROJECT | |
| TYPE | |
| NOTE | |
| PREPARED BY | |

CLA-3099

Wall-mounted Cylinder



The **CLA-3099** is a wall-mounted cylinder suitable for wet locations. With its up-and-down light features, the **CLA-3099** is perfect for giving extra luminance to any exterior location that wishes to modernize their appearance. This fixture has a wide light distribution and includes a 10 year warranty.

FEATURES

- Energy Savings: Over 66% compared to HID light sources
- Improved lumen maintenance
- Utilizes high efficient Phillips Lumiled LED's
- Operating temperatures: -30°C ~ 60°C
- Driver: Constant current, 120-277v, 50/60Hz, 480v (Optional)
- Suitable for wet locations
- Dimming, occupancy sensors, photo cell and wireless controls capable (optional)
- Optics: 24°, 50°, 78°
- Operating Life: >200,000 hours

CONSTRUCTION

- Housing is heavy-duty aluminum material
- Powder coat bronze finish (standard) various colors available (custom).
- Clear glass lens standard, prismatic glass lens optional
- Silicone gasket to prevent leakage and provide weather-tight protection.
- Mounting: Comes ready to mount on to a standard junction box.

OPTIONS

- (OCC) Motion sensor
- (PC) Button photo cell
- (WC) Wireless controls
- (PG) Prismatic glass



Buy American Compliant

| Model Number | INPUT POWER | LUMEN OUTPUT | SCOPTIC | COLOR TEMP (CCT) | CRI | RATED LIFE (L70) | INPUT VOLTAGE | INPUT FREQUENCY | HID Equivalent |
|-----------------|-------------|--------------|---------|------------------|-----|------------------|---------------|-----------------|----------------|
| CLA-3099-20CLED | 25W | 2,752 | 4,403 | 5000K | 70+ | >200,000 | 120-277V | 50/60HZ | 150w PSMH |
| CLA-3099-30CLED | 35W | 3,836 | 6,604 | 5000K | 70+ | >200,000 | 120-277V | 50/60HZ | 175w HPS |
| CLA-3099-40CLED | 45W | 5,504 | 8,806 | 5000K | 70+ | >200,000 | 120-277V | 50/60HZ | 250w MH |
| CLA-3099-60CLED | 65W | 7,672 | 13,622 | 5000K | 70+ | >200,000 | 120-277V | 50/60HZ | 250w HPS |

Ordering Guide Example: (CLA-3099-30CLED-50-MV-BZ-WC)

| CLA-3099 | WATTS | COLOR TEMP | VOLTAGE | FINISH | OPTIONS |
|-----------------|-------------------|-----------------|--------------------|--|-----------------------------|
| MODEL | | | | | |
| CLA-3099 | 20W-20CLED | 27-2700K | MV=120-277V | <u>STANDARD FINISH:</u> BZ- BRONZE | OCC- MOTION SENSOR |
| | 30W-30CLED | 30-3000K | 480-480V | | PC- BUTTON PHOTO CELL |
| | 40W-40CLED | 35-3500K | | <u>ADDITIONAL CHARGE:</u> | PG- PRISMATIC GLASS |
| | 60W-60CLED | 40-4000K | | GRY-GRAY | WC- WIRELESS CONTROL |
| | | 50-5000K | | BLK-BLACK | |
| | | 57-5700K | | WH- WHITE | |
| | 65-6500K | | CUS-CUSTOM | | |

Crystal Lighting Corporation - 13182 Flores St., Santa Fe Springs, Ca. 90670

Phone: 562-944-0223 - Fax: 562-944-0225 - WEB: www.crystallighting.us

Crystal Lighting is BUY AMERICAN compliant - All products are proudly manufactured and/or assembled in the USA