



| | |
|----------------|------|
| Job Name | |
| Catalog Number | |
| Notes | Type |

CLA-40



LENS

- Top grade opal acrylic lens
- Custom lens are available, please consult factory for minimum quantities and lead times.

HOUSING

- Can be made with almost any material.
- Comes with a standard powder coat finish.
- When powder coated, metal material goes through a degreasing process before painting. Powder coat paint is then applied and baked to ensure longevity.
- For custom finishes please consult factory.

COMPONENTS

- Ballast is electronic normal power factor and operates at 120v
- UL listed for Damp or Wet Location.
- High Power Factor and other voltages also available upon request.
- Other options include emergency back up ballast, occupancy sensors, dimming ballasts, photocells and other specifications.
- Consult factory for any special requirements or specifications.

APPLICATION

- Commonly used in residential and commercial spaces. Can be used in interior and exterior applications.



| <u>ITEM #</u> | <u>A</u> | <u>B</u> | <u>C</u> | <u>LUMENS</u> | <u>LAMPS</u> |
|---------------|----------|----------|----------|---------------|--------------|
| SM-CLA-40-60I | 11.00 in | 8.50 in | 8.00 in | 600 | 1-60W A-19 |
| SM-CLA-40-13 | 11.00 in | 8.50 in | 8.00 in | 800 | 1-13W PL |
| SM-CLA-40-26 | 11.00 in | 8.50 in | 8.00 in | 1600 | 1-26W TBX |
| MD-CLA-40-213 | 12.50 in | 9.00 in | 11.00 in | 1600 | 2-13W PL |
| MD-CLA-40-226 | 12.50 in | 9.00 in | 11.00 in | 3600 | 2-26W QUAD |
| MD-CLA-40-15 | 12.50 in | 9.00 in | 11.00 in | 1125 | 1-15W IND |
| MD-CLA-40-23 | 12.50 in | 9.00 in | 11.00 in | 1840 | 1-23W IND |
| LG-CLA-40-242 | 14.00 in | 9.50 in | 12.00 in | 6400 | 2-42W TBX |
| LG-CLA-40-42 | 14.00 in | 9.50 in | 12.00 in | 3200 | 1-42W TBX |

