



|                |      |
|----------------|------|
| Job Name       |      |
| Catalog Number |      |
| Notes          | Type |

## CLC-30



### LENS

- Top grade opal acrylic lens.
- Custom lens are available, please consult factory for minimum quantities and lead times.

### HOUSING

- Can be made with almost any material.
- Comes with a standard powder coat finish.
- When powder coated, metal material goes through a degreasing process before painting. Powder coat paint is then applied and baked to ensure longevity.
- For custom finishes please consult factory.

### COMPONENTS

- Ballast is electronic normal power factor and operates at 120v
- UL listed for Damp or Wet Location.
- High Power Factor and other voltages also available upon request.
- Other options include emergency back up ballast, occupancy sensors, dimming ballasts, photocells and other specifications.
- Consult factory for any special requirements or specifications.

### APPLICATION

- This fixture is ceiling mounted and can only be used in Damp Locations. Commonly used for decorative rooms, offices, hallways/corridors, rest-rooms and other residential and commercial spaces.



| <u>ITEM #</u>  | <u>A</u> | <u>B</u> | <u>C</u> | <u>LUMENS</u> | <u>LAMPS</u> |
|----------------|----------|----------|----------|---------------|--------------|
| SM-CLC-30-13   | 9.00 in  | 9.00 in  | 5.00 in  | 800           | 1-13W PL     |
| SM-CLC-30-26T  | 9.00 in  | 9.00 in  | 5.00 in  | 1600          | 1-26W TBX    |
| SM-CLC-30-60I  | 9.00 in  | 9.00 in  | 5.00 in  | 600           | 1-60W A-19   |
| MD-CLC-30-226Q | 11.00 in | 11.00 in | 5.00 in  | 3600          | 2-26W TBX    |
| MD-CLC-30-232T | 11.00 in | 11.00 in | 5.00 in  | 4400          | 2-32W TBX    |
| MD-CLC-30-242T | 11.00 in | 11.00 in | 5.00 in  | 6400          | 2-42W TBX    |
| MD-CLC-30-213  | 11.00 in | 11.00 in | 5.00 in  | 1600          | 2-13W PL     |
| MD-CLC-30-42T  | 11.00 in | 11.00 in | 5.00 in  | 3200          | 1-42W TBX    |
| MD-CLC-30-32T  | 11.00 in | 11.00 in | 5.00 in  | 2200          | 1-32W TBX    |

