

Job Name	
Catalog Number	
Notes	Type

CLC-3015



LENS

- Top grade opal acrylic lens.
- Custom lens are available, please consult factory for minimum quantities and lead times.

APPLICATION

• This fixture is ceiling mounted and can only be used in Damp Locations. Commonly used for decorative rooms, offices, hallways/corridors, restrooms and other residential and commercial spaces.

HOUSING

- Can be made with almost any material.
- Comes with a standard powder coat finish.
- When powder coated, metal material goes through a degreasing process before painting. Powder coat paint is then applied and baked to ensure longevity.
- For custom finishes please consult factory.

COMPONENTS

- Ballast is electronic normal power factor and operates at 120v
- UL listed for Damp Location.
- High Power Factor and other voltages also available upon request.
- Other options include emergency back up ballast, occupancy sensors, dimming ballasts, photocells and other specifications.
- Consult factory for any special requirements or specifications.



ITEM#	A	В	C	<u>LUMENS</u>	<u>LAMPS</u>
SM-CLC-3015-13	10.00 in	10.00 in	5.00 in	800	1-13W PL
SM-CLC-3015-26T	10.00 in	10.00 in	5.00 in	1600	1-26W TBX
SM-CLC-3015-60I	10.00 in	10.00 in	5.00 in	600	1-60W A-19
MD-CLC-3015-226Q	12.00 in	12.00 in	5.00 in	3600	2-26W TBX
MD-CLC-3015-232T	12.00 in	12.00 in	5.00 in	4400	2-32W TBX
MD-CLC-3015-242T	12.00 in	12.00 in	5.00 in	6400	2-42W TBX
MD-CLC-3015-213	12.00 in	12.00 in	5.00 in	1600	2-13W PL
MD-CLC-3015-42T	12.00 in	12.00 in	5.00 in	3200	1-42W TBX
MD-CLC-3015-32T	12.00 in	12.00 in	5.00 in	2200	1-32W TBX



