



DATE	
PROJECT	
TYPE	
NOTE	
PREPARED BY	

CLC-3041

CLC-3041 Induction canopy light Fixture



- Lamp Rating: 100,000 Hours for enhanced safety and maintenance
- Lumen Maintenance: 88% over 100,000 Hours
- Energy Savings: Over 57% savings comparing to HPS and other HID sources
- IP Rating: IP55, UL listed for wet location
- Light Output: 5000K, 90 CRI
- Voltage: 120- 277V standard 480V optional
- Applications: Exterior, parking areas, entrances, underpasses
- Warranty: 10 year warranty (see terms and conditions)
- Construction: Prismatic polycarbonate lens

Lamp Specifications

Wattage	Lumens	CRI	PUPIL LUMENS	CCT(KELVIN)	Rated Life
LG-CLC-3041-15IND	1,425	90	2,352	5000K	100,000 HRS
LG-CLC-3041-23IND	2,185	90	3,606	5000K	100,000 HRS

Ballast Specifications

System Wattage	Input Voltage	Input Current	Input Frequency	Power Factor	Ambient Temp	THD
18W	120-277VAC	0.15-0.06A	233KHz	.99	-31°F- 239°F	<10%
27W	120-277VAC	0.23-0.09A	233KHz	.99	-31°F- 239°F	<10%

Ordering Guide

Example: (CLC-3041-15IND-50-120V-DIM)

MODEL	WATTS	COLOR TEMP	VOLTAGE	MOUNTING	FINISH	OPTIONS
CLC-3041 CANOPY FIXTURE	15W-15IND 23W-23IND	27-2700K 35-3500K 41-4100K 50-5000K 60-6000K	120V 220V 240V 277V 120-277V	N/A	N/A	DIM-DIMMING

