



DATE	
PROJECT	
TYPE	
NOTE	
PREPARED BY	

CLC-326SM

LED Canopy Light



The **CLC-326SM** ensures strong luminosity. It displays a low profile appearance while providing safety and durability. The EZ mount structure delivers easy maintenance for contractors. A few ideal locations for the **CLC-326SM** are: hallways, entrances, underpasses and parking garages. The **CLC-326SM** offers competitive pricing and includes a 3 year warranty.

FEATURES

- Starting Temperature: -40°C
- UL & CUL listed for wet locations
- DLC listed
- Driver: Constant current, 120V
- Operating life: >50,000 hours
- 3 year warranty



CONSTRUCTION

- Solid construction die-cast aluminum body
- UV stabilized powder coat bronze finish (standard)
- Unique EZ mount design

MODEL #	INPUT POWER	LUMEN OUTPUT	SCOTOPIC	COLOR TEMP (CCT)	CRI	RATED LIFE (L70)	INPUT VOLTAGE	INPUT FREQUENCY	HID EQUIVALENT
CLC-326SM-40LED	40W	4,803	7,925	5000K	70+	>50,000	120 ~ 277V	50/60Hz	100W MH
CLC-326SM-57LED	57W	6,313	10,417	5000K	70+	>50,000	120 ~ 277V	50/60Hz	100W-150W MH

Ordering Guide

Example: CLC-326SM-57LED-50-MV-BZ-EZ

CLC-326SM

MODEL	WATTS	COLOR TEMP	VOLTAGE	FINISH	MOUNTING
CLC-326SM	40W-40LED 57W-57LED	50-5000K	MV—120-277V	BZ- BRONZE	EZ-EZ MOUNT

Dimensions

