



DATE	
PROJECT	
TYPE	
NOTE	
PREPARED BY	

CLC-333SM

LED Canopy Light



The **CLC-333SM** ensures strong luminosity and durability. A few ideal locations for the **CLC-333SM** are: hallways, entrances, underpasses and parking garages. The EZ mount structure delivers easy installation for contractors. The **CLC-333SM** offers competitive pricing and includes a 3 year warranty.



FEATURES

- Starting Temperature: -40°C
- UL & CUL listed for wet locations
- 4700K
- Driver: Constant current, 120~277V
- Operating life: >100,000 hours
- 3 year warranty

CONSTRUCTION

- Solid construction die-cast aluminum body
- Powder coat white finish (standard)
- Unique EZ mount design

MODEL #	INPUT POWER	LUMEN OUTPUT	SCOTOPIC	COLOR TEMP (CCT)	CRI	RATED LIFE (L70)	INPUT VOLTAGE	INPUT FREQUENCY
CLC-333SM-55LED	55W	5,700	9,405	4700K	80+	>100,000	120 ~ 277V	50/60Hz
CLC-333SM-94LED	94W	9,480	15,642	4700K	80+	>100,000	120 ~ 277V	50/60Hz
CLC-333SM-142LED	142W	13,451	22,194	4700K	80+	>100,000	120 ~ 277V	50/60Hz

Ordering Guide

Example: CLC-333SM-55LED-47-MV-WH-EZ

CLC-333SM					
MODEL	WATTS	COLOR TEMP	VOLTAGE	FINISH	MOUNTING
CLC-333SM	55W-55LED 94W-94LED 142W-142LED	47-4700K	MV=120~277V	WH-WHITE	EZ-EZ MOUNT

Dimensions

