



DATE	
PROJECT	
TYPE	
NOTE	
PREPARED BY	

## CLC-CUATRO

## LED Canopy Light



The **CLC-CUATRO** ensures strong luminosity. It displays a low profile appearance while providing safety and durability. A few ideal locations for the **CLC-CUATRO** are: hallways, entrances, underpasses and parking garages. The EZ mount structure delivers easy installation for contractors. The **CLC-CUATRO** offers competitive pricing and includes a 3 year warranty.

### FEATURES

- Starting Temperature: 40°C
- UL & CUL listed for wet locations
- DLC listed
- Suitable for wet locations
- Driver: Constant current, 120~277V
- Operating life: >50,000 hours



### CONSTRUCTION

- Solid construction die-cast aluminum body
- Powder coat gray finish (standard)
- Unique EZ mount design

MODEL #	INPUT POWER	LUMEN OUTPUT	SCOTOPIC	COLOR TEMP (CCT)	CRI	RATED LIFE (L70)	INPUT VOLTAGE	INPUT FREQUENCY
CLC-CUATRO-55LED	55W	5,100	8,415	5000K	80+	>50,000	120 ~ 277V	50/60Hz

## Ordering Guide

Example: CLC-CUATRO-55LED-50-MV-GR-EZ

CLC-CUATRO					
MODEL	WATTS	COLOR TEMP	VOLTAGE	FINISH	MOUNTING
CLC-CUATRO	55W-55LED	50-5000K	MV=120-277V	GR-GRAY	EZ-EZ MOUNT

# Dimensions

