



Job Name

Catalog Number

Notes

Type

CLH-20



LENS

- Top grade opal acrylic lens.
- Custom lens are available, please consult factory for minimum quantities and lead times.

HOUSING

- Can be made with almost any material.
- Comes with a standard powder coat finish.
- When powder coated, metal material goes through a degreasing process before painting. Powder coat paint is then applied and baked to ensure longevity.
- For custom finishes please consult factory.

COMPONENTS

- Ballast is electronic normal power factor and operates at 120v
- UL listed for Damp Location. Wet location is optional.
- High Power Factor and other voltages also available upon request.
- Other options include emergency back up ballast, occupancy sensors, dimming ballasts, photocells and other specifications.
- Consult factory for any special requirements or specifications.

APPLICATION

- The majority of hanging fixtures are placed in interior applications. Therefore, they are listed for Damp location. Fixture can also be made for Wet location upon request. Popular applications include restaurants, walkways/hallways, restrooms/bathrooms and other residential and commercial applications.



| <u>ITEM #</u> | <u>A</u> | <u>B</u> | | <u>LUMENS</u> | <u>LAMPS</u> |
|----------------|----------|----------|---------|---------------|--------------|
| SM-CLH-20-60I | 11.00 in | 7.00 in | 0.00 in | 600 | 1-60I INC |
| SM-CLH-20-13 | 11.00 in | 7.00 in | 0.00 in | 800 | 1-13W PL |
| SM-CLH-20-26T | 11.00 in | 7.00 in | 0.00 in | 1800 | 1-26W TBX |
| MD-CLH-20-213 | 12.50 in | 8.50 in | 0.00 in | 1600 | 2-13W PL |
| LG-CLH-20-242T | 14.00 in | 9.50 in | 0.00 in | 3200 | 2-42W TBX |
| MD-CLH-20-226Q | 12.50 in | 8.50 in | 0.00 in | 3600 | 2-26W QUAD |
| LG-CLH-20-42T | 14.00 in | 9.50 in | 0.00 in | 3200 | 1-42W TBX |
| MD-CLH-20-15 | 12.50 in | 8.50 in | 0.00 in | 1125 | 1-15 INDUC |
| MD-CLH-20-23 | 12.50 in | 8.50 in | 0.00 in | 1845 | 1-23W INDUC |

