



Job Name	
Catalog Number	
Notes	Type

## CLH-60



### LENS

- Top grade opal acrylic lens.
- Custom lens are available, please consult factory for minimum quantities and lead times.

### HOUSING

- Can be made with almost any material.
- Comes with a standard powder coat finish.
- When powder coated, metal material goes through a degreasing process before painting. Powder coat paint is then applied and baked to ensure longevity.
- For custom finishes please consult factory.

### COMPONENTS

- Ballast is electronic normal power factor and operates at 120v
- UL listed for Damp Location. Wet location is optional.
- High Power Factor and other voltages also available upon request.
- Other options include emergency back up ballast, occupancy sensors, dimming ballasts, photocells and other specifications.
- Consult factory for any special requirements or specifications.

### APPLICATION

- The majority of hanging fixtures are placed in interior applications. Therefore, they are listed for Damp location. Fixture can also be made for Wet location upon request. Popular applications include restaurants, walkways/hallways, restrooms/bathrooms and other residential and commercial applications.



<u>ITEM #</u>	<u>A</u>	<u>B</u>		<u>LUMENS</u>	<u>LAMPS</u>
SM-CLH-60-60I	12.00 in	7.00 in	0.00 in	600	1-60I INC
SM-CLH-60-13	12.00 in	7.00 in	0.00 in	800	1-13W PL
SM-CLH-60-26T	12.00 in	7.00 in	0.00 in	1800	1-26W TBX
MD-CLH-60-213	14.00 in	9.00 in	0.00 in	1600	2-13W PL
LG-CLH-60-242T	16.00 in	12.00 in	0.00 in	3200	2-42W TBX
MD-CLH-60-226Q	14.00 in	9.00 in	0.00 in	3600	2-26W QUAD
LG-CLH-60-42T	16.00 in	12.00 in	0.00 in	3200	1-42W TBX
MD-CLH-60-15	14.00 in	9.00 in	0.00 in	1125	1-15 INDUC
MD-CLH-60-23	14.00 in	9.00 in	0.00 in	1845	1-23W INDUC

