



Job Name

Catalog Number

Notes

Type

## CLP-17



### LENS

- Top grade opal acrylic lens.
- Custom lens are available, please consult factory for minimum quantities and lead times.

### HOUSING

- Can be made with almost any material.
- Comes with a standard powder coat finish.
- When powder coated, metal material goes through a degreasing process before painting. Powder coat paint is then applied and baked to ensure longevity.
- For custom finishes please consult factory.

### COMPONENTS

- Ballast is electronic normal power factor and operates at 120v
- UL listed for Damp or Wet Location.
- High Power Factor and other voltages also available upon request.
- Other options include emergency back up ballast, occupancy sensors, dimming ballasts, photocells and other specifications.
- Consult factory for any special requirements or specifications.

### APPLICATION

- Post fixtures like their name gives away, are mounted on a post and usually occupy space in exterior applications. Although they are still used in interior spaces, common places of application for this fixture include parks, walkways, shopping centers, business exteriors and other residential and commercial spaces.



| <u>ITEM #</u>  | <u>A</u> | <u>B</u> |         | <u>LUMENS</u> | <u>LAMPS</u> |
|----------------|----------|----------|---------|---------------|--------------|
| SM-CLP-17-13   | 17.50 in | 9.00 in  | 0.00 in | 800           | 1-13W PL     |
| SM-CLP-17-26T  | 17.50 in | 9.00 in  | 0.00 in | 1600          | 1-26W TBX    |
| SM-CLP-17-60I  | 17.50 in | 9.00 in  | 0.00 in | 600           | 1-60W A-19   |
| LG-CLP-17-226Q | 21.50 in | 10.00 in | 0.00 in | 3600          | 2-26W TBX    |
| SM-CLP-17-15   | 17.50 in | 9.00 in  | 0.00 in | 1125          | 1-15W INDUC  |
| SM-CLP-17-23   | 17.50 in | 9.00 in  | 0.00 in | 1840          | 1-23W INDUC  |
| LG-CLP-17-213  | 21.50 in | 10.00 in | 0.00 in | 1600          | 2-13W PL     |
| LG-CLP-17-42T  | 21.50 in | 10.00 in | 0.00 in | 3200          | 1-42W TBX    |
| LG-CLP-17-242T | 21.50 in | 10.00 in | 0.00 in | 6400          | 2-42W TBX    |

