



DATE	
PROJECT	
TYPE	
NOTE	
PREPARED BY	

CLP-3040

LED Flood/Area Light



The **CLP-3040** is strongly built with precision die cast aluminum and with a chip/fade resistant powder coat finish. It is suitable for various outdoor environments. The **CLP-3040** is commonly ideal for: wall washing, parking areas, entrances, walkways, and underpasses. The **CLP-3040** offers competitive pricing and includes a 5 year warranty.

FEATURES

- CRI: 80
- Starting Temperature: -30°C ~ 60°C
- UL & CUL listed for wet locations
- IP66, rated outdoor use
- 4000K
- 120~277V
- Operating life: >100,000 hours
- 5 year warranty



OPTIONS

- (OCC) Motion Sensor

CONSTRUCTION

- Precision die cast
- Aluminum and acrylic reflector
- Chip and fade resistant powder coat finish; bronze finish (standard)

MODEL #	INPUT POWER	LUMEN OUTPUT	SCOTOPIC	COLOR TEMP (CCT)	CRI	RATED LIFE (L70)	INPUT VOLTAGE	INPUT FREQUENCY
CLP-3040-250LED	250W	27,935	46,093	4000K	70	>100,000	120~277V	50/60 Hz
CLP-3040-300LED	300W	34,284	56,568	4000K	70	>100,000	120~277V	50/60 Hz

Ordering Guide

Example: CLP-3040-300LED-40-SB-MV-BZ

CLP-3040

MODEL	WATTS	COLOR TEMP	MOUNTING	VOLTAGE	FINISH
CLP-3040	250W-250LED	40-4000K	SB-SWIVEL BRACKET	MV=120~277V	BZ-BRONZE
	300W-300LED		SF-SLIP FITTER		

Dimensions

