



DATE	
PROJECT	
TYPE	
NOTE	
PREPARED BY	

CLP-3040

LED Flood Area

The energy efficient LED light fixture, **CLP-3040** is durable, reliant and provides powerful luminosity. It is ideal for: parking structures, walkways, and underpasses. The **CLP-3040** offers competitive pricing and includes a 3 year warranty.



FEATURES

- CRI: 80
- -30°C ~ 60°C
- UL & CUL listed for wet locations
- IP rating: IP66
- Driver: Constant current, 120~277V
- Operating life: >100,000 hours

CONSTRUCTION

- Precision die cast
- Aluminum and acrylic reflector
- Bronze (standard) finish

OPTIONS

- (OCC) Motion Sensor

MODEL #	INPUT POWER	DELIVERED LUMENS	SCOTOPIC	COLOR TEMP (CCT)	CRI	RATED LIFE (L70)	INPUT VOLTAGE	INPUT FREQUENCY
CLP-3040-250LED	250W	27,935	46,093	5000K	80	>50,000	120V	50/60Hz
CLP-3040-300LED	300W	34,284	56,568	5000K	80	>50,000	120V	50/60Hz
CLP-3040-400LED	400W	44,723	73,793	5000K	80	>50,000	120V	50/60Hz

Ordering Guide

Example: CLP-3040-300LED-50-MV-BZ-SF

MODEL	WATTS	COLOR TEMP	VOLTAGE	FINISH	MOUNTING
CLP-3040	250W-250LED	50-5000K	MV-120-277V	BZ-BRONZE	SB-SWIVEL BRACKET
	300W-300LED				SF-SLIP FITTER
	400W-400LED				

Dimensions

