



DATE	
PROJECT	
TYPE	
NOTE	
PREPARED BY	

CLP-SL-257 LED Post Top fixture



The **CLP-SL-257** differentiates from other LED Post top fixtures due to its creative shape and internal efficiency. The **CLP-SL-257** is suitable for outdoor, wet locations. It is essential for illuminating residential exteriors, walkways, perimeters, school campuses, commercial spaces, parking lots, and recreational parks. This fixture has various light distribution options. The investment of a **CLP-SL-257** includes a 10 year/50,000hr limited warranty.

FEATURES

- Energy Savings: Over 66% compared to HID light sources
- Improved lumen maintenance
- Utilizes high efficient Phillips Lumiled LED's
- Operating temperatures: -30°C ~ 60°C
- Driver: Constant current, 120~277v, 50/60Hz, 480v (Optional)
- Suitable for wet locations
- Dimming, occupancy sensors, photo cell and wireless controls capable (optional)
- Operating Life: >200,000 hours

CONSTRUCTION

- Housing is heavy-duty die-cast aluminum material
- Powder coat finish (standard)
- Clear Seedy acrylic (standard), clear tempered glass lens (optional)
- Silicone gasket to prevent leakage and provide weather-tight protection.
- Mounting: Comes ready to mount on top of a 3" round pole (standard) can be built to mount on other size poles and shapes.

OPTIONS

- (OCC) Motion sensor
- (PC) Button photo cell
- (WC) Wireless controls
- (TYPE3) Type III OPTIC
- (TYPE4) Type IV OPTIC
- (TYPE5) Type V OPTIC
- (CSA) Clear Seedy Acrylic
- (OA) Opal Acrylic
- (FA) Frosted Acrylic Lens



Model Number	INPUT POWER	LUMEN OUTPUT	SCOPTIC	COLOR TEMP (CCT)	CRI	RATED LIFE (L70)	INPUT VOLTAGE	INPUT FREQUENCY	HID Equivalent
CLP-SL-257-35CLED	42W	5,022	8,286	5000K	70+	>200,000	120-277V	50/60HZ	175w HPS
CLP-SL-257-75CLED	84W	10,044	16,573	5000K	70+	>200,000	120-277V	50/60HZ	250w HPS
CLP-SL-257-90CLED	97W	13,193	21,768	5000K	70+	>200,000	120-277v	50/60Hz	400w PSMH
CLP-SL-257-120CLED	129W	17,591	29,025	5000K	70+	>200,000	120-277v	50-60Hz	400w HPS

Ordering Guide Example: (CLP-SL-257-35CLED-50-MV-BZ-OA-TYP5)

CLP-SL-257	MODEL	WATTS	COLOR TEMP	VOLTAGE	FINISH	LENS	OPTIONS
	CLP-SL-257	35W-35CLED 75W-75CLED 90W-90CLED 120W-120CLED	27-2700K 30-3000K 35-3500K 40-4000K 50-5000K 57-5700K 65-6500K	MV=120-277V 480-480V	BZ- BRONZE GRY-GRAY BLK-BLACK WH- WHITE CUS-CUSTOM	CSA-CLEAR SEEDY ACRYLIC OA- OPAL ACRYLIC FA- FROSTED ACRYLIC CUS-CUSTOM NL- NO LENS	OCC- MOTION SENSOR PC- BUTTON PHOTO CELL WC- WIRELESS CONTROL TYPE3- TYPE III OPTIC TYPE4-TYPE IV OPTIC TYPE5- TYPE V OPTIC

Crystal Lighting Corporation - 13182 Flores St., Santa Fe Springs, Ca. 90670

Phone: 562-944-0223 - Fax: 562-944-0225 - WEB: www.crystallighting.us

Crystal Lighting is BUY AMERICAN compliant - All products are proudly manufactured and/or assembled in the USA

Ordering Guide

