



DATE	
PROJECT	
TYPE	
NOTE	
PREPARED BY	

**CLP-SL-X50**

**LED Pole Mount Fixture**



The **CLP-SL-X50** has an elegant design that adds style and class to any location. A few locations that this fixture is suitable for are: townships, parks, walkways, housing communities, and driveways. Internally, the **CLP-SL-X50** is durable, reliable and designed to tolerate wet locations. A 10 year/100,000 hour limited warranty is included along with your investment.

**FEATURES**

- Energy Savings: Over 60% compared to HID light sources
- Improved lumen maintenance
- Manufactured with high efficient Lumiled® LED'S
- Operating Temperatures: -30°C ~ 60°C
- Driver: Constant current, 120-277v, 50/60Hz, 347/480v (Optional)
- Suitable for wet locations
- Operating life: >200,000 hours

**CONSTRUCTION**

- Housing is heavy-duty die-cast aluminum
- Powder coat bronze finish (standard) various colors available (custom/add'l cost)
- Clear glass lens (standard), frosted acrylic lens (optional)
- Silicone gasket to prevent leakage and provide weather-tight protection
- Mounting: Mounting: Comes ready to mount on top of a 3" round pole (standard), 4" round pole (optional)

**OPTIONS**

- (PC) Button Photo Cell
- (HSS) House Side Shield
- (WC) Wireless Controls
- (MG) Marine Grade Finish

PHILIPS  
LUMILEDS

NEMA

0-10v  
Dimmable

Wireless Controls  
Available



MODEL #	INPUT POWER	SYSTEM LUMENS	COLOR TEMP (CCT)	CRI	RATED LIFE (L70)	INPUT VOLTAGE	INPUT FREQUENCY
CLP-SL-X50-30CLED	35W	5,328	5000K	70+	>200,000	120~277V	50/60Hz
CLP-SL-X50-50CLED	54W	7,320	5000K	70+	>200,000	120~277V	50/60Hz
CLP-SL-X50-70CLED	70W	11,968	5000K	70+	>200,000	120~277V	50/60Hz
CLP-SL-X50-100CLED	105W	14,640	5000K	70+	>200,000	120~277V	50/60Hz

# Ordering Guide

Example: CLP-SL-X50-40CLELED-50-MV-BZ-3-T3-PC

CLP-SL-X50							
MODEL	WATTS	COLOR TEMP	VOLTAGE	FINISH	MOUNTING	Distribution Type	OPTIONS
<b>CLP-SL-X50</b>	30W-30CLELED	30-3000K	<b>MV=120-277V</b>	<b>BZ- BRONZE</b>	<b>(3) 3" ROUND POST FITTER</b>	T3- Type III	<b>PC-BUTTON PHOTO CELL</b>
	40W-40CLELED	40-4000K		GRY-GRAY	(4) 4" ROUND POST FITTER	T4- Type IV	HSS-HOUSE SIDE SHIELD
	<b>50W-50CLELED</b>	<b>50-5000K</b>		BLK-BLACK	(5) 2/8" ROUND POST FITTER	T5- Type V	WC-WIRELESS CONTROLS
	60W-60CLELED			WH- WHITE			MG-MARINE GRADE FINISH
	70W-70CLELED			CUS-CUSTOM			FAL-FROSTED ACRYLIC LENS
	100W-100CLELED					NL- NO LENS	

## Dimensions

