



| | |
|----------------|------|
| Job Name | |
| Catalog Number | |
| Notes | Type |

CLW-2076



LENS

- Top grade opal acrylic lens.
- Standard size
- Custom lens are available, please consult factory for minimum quantities and lead times.

APPLICATION

- Commonly used in residential and commercial spaces. Can be used in interior or exterior applications.

HOUSING

- Can be made with almost any material.
- Comes with a brushed aluminum or powder coat finish.
- When powder coated, metal material goes through a degreasing process before painting. Powder coat paint is then applied and baked to ensure longevity.
- For custom finishes please consult factory.

COMPONENTS

- Ballast is electronic normal power factor and operates at 120v
- UL listed for Damp and Wet Location.
- High Power Factor and other voltages also available upon request.
- Other options include emergency back up ballast, occupancy sensors, dimming ballasts, photocells and other specifications.
- Consult factory for any special requirements or specifications.





| ITEM # | A | B | C | LUMENS | LAMPS |
|-----------------|----------|----------|---------|--------|------------|
| SM-CLW-2076-60I | 9.00 in | 9.00 in | 4.00 in | 600 | 1-60W A-19 |
| SM-CLW-2076-13 | 9.00 in | 9.00 in | 4.00 in | 800 | 1-13W PL |
| SM-CLW-2076-26 | 9.00 in | 9.00 in | 4.00 in | 1800 | 1-26W TBX |
| MD-CLW-2076-213 | 12.00 in | 12.00 in | 4.00 in | 1600 | 2-13W PL |
| MD-CLW-2076-226 | 12.00 in | 12.00 in | 4.00 in | 3600 | 2-26W QUAD |
| MD-CLW-2076-15 | 12.00 in | 12.00 in | 4.00 in | 1125 | 1-15W IND |
| MD-CLW-2076-23 | 12.00 in | 12.00 in | 4.00 in | 1840 | 1-23W IND |
| LG-CLW-2076-32 | 16.00 in | 16.00 in | 4.00 in | 2400 | 1-32W TBX |
| LG-CLW-2076-42 | 16.00 in | 16.00 in | 4.00 in | 3200 | 1-42W TBX |
| LG-CLW-2076-27 | 16.00 in | 16.00 in | 4.00 in | 1800 | 1-27W BIAX |
| LG-CLW-2076-227 | 16.00 in | 16.00 in | 4.00 in | 3600 | 2-27W BIAX |

