

DATE	
PROJECT	
TYPE	
NOTE	
PREPARED BY	

## CLW-3033

## Small forward throw LED wallpack

Small forward throw LED wall pack fixture, suitable for wet locations, Perfect for lighting up residential exteriors, walkways, entry ways, perimeters, parking garages, school campuses, industrial/commercial spaces. This fixture has a wide rectangular light distribution. Comes with a 5 year/50,000 hour limited warranty.



### FEATURES

- Energy Savings: Over 66% compared to HID light sources
- Improved lumen maintenance
- Utilizes high efficient Phillips Lumiled LED's
- Operating temperatures: -30°C ~ 60°C
- Driver: Constant current, 120-277v, 50/60Hz, 480v (Optional)
- Suitable for wet locations
- Dimming, occupancy sensors, photo cell capable (optional)
- Operating Life: >200,000 hours

### CONSTRUCTION

- Back plate is heavy-duty die-cast aluminum material
- 1/2" Coin plugs with O-rings for conduit, sensors or photo cell
- Powder coat bronze finish
- Prismatic borosilicate glass lens
- Silicone gasket to prevent leakage and provide weather-tight protection.
- Mounting: Cast-in Template for Mounting Directly Over a 4" Recessed Outlet Box or use 1/2" Surface Conduit

### OPTIONS

- (PC) Button photo cell
- (WC) Wireless Controls
- (FCV) Full cutoff visor
- (GS) Glare shield
- (WG) Wire guard



Model Number	INPUT POWER	LUMEN OUTPUT	SCOPTIC	COLOR TEMP (CCT)	CRI	RATED LIFE (L70)	INPUT VOLTAGE	INPUT FREQUENCY	HID Equivalent
CLW-3033-5CLED	7W	757	1,211	5000K	70+	>200,000	120-277V	50/60HZ	35w HPS
CLW-3033-10CLED	12W	1,376	2,201	5000K	70+	>200,000	120-277V	50/60HZ	50w HPS
CLW-3033-15CLED	20W	1,918	3,068	5000K	70+	>200,000	120-277V	50/60HZ	70w HPS
CLW-3033-20CLED	25W	2,752	4,403	5000K	70+	>200,000	120-277V	50/60HZ	100w MH
CLW-3033-30CLED	35W	4,128	6,604	5000K	70+	>200,000	120-277V	50/60HZ	150w MH
CLW-3033-40CLED	45W	5,504	8,806	5000K	70+	>200,000	120-277V	50/60HZ	175w MH

# Ordering Guide

Example: (CLW-3033-40CLED-50-MV-BZ-WG)

MODEL	WATTS	COLOR TEMP	VOLTAGE	FINISH	OPTIONS
CLW-3033	5W-5CLED 10W-10CLED 15W-15CLED 20W-20CLED 30W-30CLED <b>40W-40CLED</b>	27-2700K 30-3000K 35-3500K 40-4000K <b>50-5000K</b> 57-5700K	MV=120-277V 480-480V	<u>STANDARD:</u> <b>BZ- BRONZE</b>  <u>ADD'L COST:</u> GRY-GRAY BLK-BLACK WH-WHITE CUS-CUSTOM	PC- BUTTON PHOTO CELL WC- WIRELESS CONTROL FCV- FULL CUTOFF VISOR GS- GLARE SHIELD <b>WG- WIRE GUARD</b>

# Dimensions

