



crystal lighting
CORPORATION

DATE	
PROJECT	
TYPE	
NOTE	
PREPARED BY	

CLW-3038



CLW-3038 Induction Canopy Fixture

- Lamp Rating: 100,000 Hours for enhanced safety and maintenance
- Lumen Maintenance: 88% over 100,000 Hours
- Energy Savings: Over 57% savings comparing to HPS and other HID sources
- IP Rating: IP55, UL listed for wet location
- Light Output: 5000K, 90 CRI
- Voltage: 120-277v Standard, 480v Optional
- Applications: Exterior walls, parking areas, entrances, walkways, underpasses
- Warranty: 10 year warranty (see terms and conditions)
- Construction: Heavy duty die cast aluminum body, clear prismatic polycarbonate lens

Lamp Specifications

Wattage	Lumens	CRI	Pupil Lumens	CCT(KELVIN)	Rated Life
CLW-3038-80IND	7,600	90	12,540	5000k	100,000 hours
CLW-3038-100IND	9,500	90	15,675	5000k	100,000 hours
CLW-3038-120IND	11,400	90	18,810	5000k	100,000 hours

Ballast Specifications

System Wattage	Input Voltage	Input Current	Input Frequency	Power Factor	Ambient Temp	THD
84W	120-277VAC	0.7-0.30A	233 KHz	0.99	-31°F-239°F	<10 %
105W	120-277VAC	0.87-0.37A	233 KHz	0.99	-31°F-239°F	<10 %
126W	120-277VAC	1.05-0.45A	233 KHz	0.99	-31°F-239°F	<10 %

Ordering Guide

Example: (LG-CLW-3038-80IND-50-120V-BZ-PC)

MODEL	WATTS	COLOR TEMP	VOLTAGE	MOUNTING	FINISH	OPTIONS
CLW-3038 CANOPY	80W-80IND 100W-100IND 120W-120IND	27-2700K 35-3500K 41-4100K 50-5000K 60-6000K	120V 220V 240V 277V 120-277V	N/A	BZ- BRONZE WHT-WHITE BLK-BLACK SIL-SILVER CUS-CUSTOM	PC-PHOTO CELL GS-GLARE SHIELD BFL-BAFFLE/VISOR DIM-DIMMING

