



| | |
|----------------|------|
| Job Name | |
| Catalog Number | |
| Notes | Type |

CLW-90



LENS

- Top Grade opal acrylic lens.
- Standard size
- Custom lens are available, please consult factory for minimum quantities and lead times.

APPLICATION

- Commonly used in residential and commercial spaces. Can be used in interior or exterior applications.

HOUSING

- Can be made with almost any material.
- Comes with powder coat finish.
- When powder coated, metal material goes through a degreasing process before painting. Powder coat paint is then applied and baked to ensure longevity.
- For custom finishes please consult factory.

COMPONENTS

- Ballast is electronic normal power factor and operates at 120v
- UL listed for Damp and Wet location.
- High Power Factor and other voltages also available upon request.
- Other options include emergency back up ballast, occupancy sensors, dimming ballasts, photocells and other specifications.
- Consult factory for any special requirements or specifications.



| ITEM # | A | B | C | LUMENS | LAMPS |
|---------------|----------|---------|---------|--------|------------|
| SM-CLW-90-60I | 10.00 in | 7.00 in | 4.00 in | 600 | 1-60W A-19 |
| SM-CLW-90-13 | 10.00 in | 7.00 in | 4.00 in | 800 | 1-13W PL |
| SM-CLW-90-26 | 10.00 in | 7.00 in | 4.00 in | 1600 | 1-26W TBX |
| MD-CLW-90-213 | 12.50 in | 8.50 in | 4.00 in | 1600 | 2-13W PL |
| MD-CLW-90-226 | 12.50 in | 8.50 in | 4.00 in | 3600 | 2-26W QUAD |
| MD-CLW-90-15 | 12.50 in | 8.50 in | 4.00 in | 1125 | 1-15W IND |
| MD-CLW-90-23 | 12.50 in | 8.50 in | 4.00 in | 1840 | 1-23W IND |
| LG-CLW-90-27 | 16.00 in | 9.00 in | 5.00 in | 1800 | 1-27W BIAX |
| LG-CLW-90-227 | 16.00 in | 9.00 in | 5.00 in | 3600 | 2-27W BIAX |

