



|                |      |
|----------------|------|
| Job Name       |      |
| Catalog Number |      |
| Notes          | Type |

## CLW-SLP



### LENS

- Top grade opal acrylic lens.
- Standard size
- Custom lens are available, please consult factory for minimum quantities and lead times.

### APPLICATION

- Commonly used in residential and commercial spaces. Can be used in interior or exterior applications.

### HOUSING

- Can be made with almost any material.
- Comes with a brushed aluminum or powder coat finish.
- When powder coated, metal material goes through a degreasing process before painting. Powder coat paint is then applied and baked to ensure longevity.
- For custom finishes please consult factory.

### COMPONENTS

- Ballast is electronic normal power factor and operates at 120v
- UL listed for Damp and Wet Location.
- High Power Factor and other voltages also available upon request.
- Other options include emergency back up ballast, occupancy sensors, dimming ballasts, photocells and other specifications.
- Consult factory for any special requirements or specifications.





| <u>ITEM #</u>  | <u>A</u> | <u>B</u> | <u>C</u>                                                 | <u>LUMENS</u> | <u>LAMPS</u> |
|----------------|----------|----------|----------------------------------------------------------|---------------|--------------|
| SM-CLW-SLP-60I | 10.00 in | 7.50 in  | 4.00 in                                                  | 600           | 1-60W A-19   |
| SM-CLW-SLP-13  | 10.00 in | 7.50 in  | 4.00 in                                                  | 800           | 1-13W PL     |
| SM-CLW-SLP-26  | 10.00 in | 7.50 in  | 4.00 in                                                  | 1800          | 1-26W TBX    |
| MD-CLW-SLP-213 | 12.00 in | 9.00 in  | 4.00 in                                                  | 1600          | 2-13W PL     |
| MD-CLW-SLP-226 | 12.00 in | 9.00 in  | 4.00 in                                                  | 3600          | 2-26W QUAD   |
| MD-CLW-SLP-15  | 12.00 in | 9.00 in  | 4.00 in                                                  | 1125          | 1-15W IND    |
| MD-CLW-SLP-23  | 12.00 in | 9.00 in  | 4.00 in                                                  | 1840          | 1-23W IND    |
| LG-CLW-SLP-32  | 16.00 in | 11.00 in | 5.00 in                                                  | 2400          | 1-32W TBX    |
| LG-CLW-SLP-42  | 16.00 in | 11.00 in | 5.00 in dimension="500" <td>3200</td> <td>1-42W TBX</td> | 3200          | 1-42W TBX    |
| LG-CLW-SLP-27  | 16.00 in | 11.00 in | 5.00 in                                                  | 1800          | 1-27W BIAX   |
| LG-CLW-SLP-227 | 16.00 in | 11.00 in | 5.00 in                                                  | 3600          | 2-27W BIAX   |

