



CRYSTAL SIGNATURE  
CRYSTAL SIGNATURE

**SL-CLP-X-43**

**Acorn LED area light fixture**



\*\*shown in custom finish

The SL-CLP-X-43 is an architectural LED area light fixture constructed with rugged die-cast aluminum. It includes a standard acrylic lens and is suitable for wet locations. Perfect for lighting up residential exteriors, walkways, perimeters, school campuses, industrial/commercial spaces, parking lots, recreational parks. This fixture has a wide light distribution and has a high L70 rating of 200,000 hours. The SL-CLP-X-43 includes a 10 year warranty.

**FEATURES**

- Energy Savings: Over 66% compared to HID light sources
- Improved lumen maintenance
- Utilizes high efficient Phillips Lumiled LED's
- Operating temperatures: -30°C ~ 60°C
- Driver: Constant current, 120-277v, 50/60Hz, 480v (Optional)
- Suitable for wet locations
- Dimming, occupancy sensors, photo cell and wireless controls capable (optional)
- Operating Life: >200,000 hours

**CONSTRUCTION**

- Housing is heavy-duty die-cast aluminum base
- Powder coat bronze finish (standard) various colors available (custom).
- Clear prismatic acrylic Type 5 (standard), clear prismatic polycarbonate lens (optional)
- Silicone gasket to prevent leakage and provide weather-tight protection.
- Mounting: Comes ready to mount on top of a 3" round pole (standard) 4" round pole adapter is optional

**OPTIONS**

- (PC) Button photo cell
- (WC) Wireless controls
- (TYP3) Type 3 lens
- (TYP5) Type 5 lens
- (PLY) Polycarbonate lens
- (DF) Decorative Finial
- (ST) Solid Top

| Model Number       | INPUT POWER | LUMEN OUTPUT | SCOPTIC | COLOR TEMP (CCT) | CRI | RATED LIFE (L70) | INPUT VOLTAGE | INPUT FREQUENCY | HID Equivalent |
|--------------------|-------------|--------------|---------|------------------|-----|------------------|---------------|-----------------|----------------|
| SL-CLP-X-43-20CLED | 25W         | 2,750        | 4,530   | 5000K            | 70+ | >200,000         | 120-277V      | 50/60HZ         | 100w MH        |
| SL-CLP-X-43-40CLED | 45W         | 5,504        | 8,806   | 5000K            | 70+ | >200,000         | 120-277V      | 50/60HZ         | 150w HPS       |
| SL-CLP-X-43-60CLED | 65W         | 8,256        | 13,622  | 5000K            | 70+ | >200,000         | 120-277V      | 50/60HZ         | 250w PSMH      |
| SL-CLP-X-43-75CLED | 80W         | 9,590        | 15,344  | 5000K            | 70+ | >200,000         | 120-277V      | 50/60HZ         | 250w HPS       |

# Ordering Guide

Example: (SL-CLP-X-43-40CLED-50-MV-BZ-TYP5-WC)

## SL-CLP-X-43

| MODEL       | WATTS      | COLOR TEMP | VOLTAGE      | FINISH     | OPTIONS                |
|-------------|------------|------------|--------------|------------|------------------------|
| SL-CLP-X-43 | 25W-25CLED | 27-2700K   | MV: 120-277V | BZ- BRONZE | OCC- MOTION SENSOR     |
|             | 40W-40CLED | 30-3000K   | 480-480V     | GRY-GRAY   | PC- BUTTON PHOTO CELL  |
|             | 60W-60CLED | 35-3500K   |              | BLK-BLACK  | WC- WIRELESS CONTROL   |
|             | 80W-80CLED | 40-4000K   |              | WH- WHITE  | TYP3- TYPE 3 LENS      |
|             |            | 50-5000K   |              | CUS-CUSTOM | TYP5- TYPE 5 LENS      |
|             |            | 57-5700K   |              |            | PLY-Polycarbonate lens |
|             |            | 65-6500K   |              |            | DF- Decorative finial  |
|             |            |            |              |            | ST- Solid Top          |

# dimensions

