



DATE	
PROJECT	
TYPE	
NOTE	
PREPARED BY	

SL-MS

LED Pole Mount Fixture



The **SL-MS** has an elegant design that adds style and class to any location. A few locations that this fixture is suitable for are: townships, parks, walkways, housing communities, and driveways. Internally, the **SL-MS** is durable, reliable and designed to tolerate wet locations. A 10 year/100,000 hour limited warranty is included along with your investment.

FEATURES

- Energy Savings: Over 60% compared to HID light sources
- Improved lumen maintenance
- Manufactured with high efficient Lumiled® LED'S
- Operating Temperatures: -30°C ~ 60°C
- Driver: Constant current, 120-277v, 50/60Hz, 480v (Optional)
- Suitable for wet locations
- Operating life: >200,000 hours

CONSTRUCTION

- Housing is heavy-duty die-cast aluminum
- Powder coat bronze finish (standard) various colors available (custom/add'l cost)
- Clear glass lens (standard), frosted acrylic lens (optional)
- Silicone gasket to prevent leakage and provide weather-tight protection
- Mounting: Mounting: Comes ready to mount on top of a 3" round pole (standard), 4" round pole (optional)

OPTIONS

- (PC) Button Photo Cell
- (HSS) House Side Shield
- (WC) Wireless Controls
- (MG) Marine Grade Finish
- (FAL) Frosted Acrylic Lens



MODEL #	INPUT POWER	LUMEN OUTPUT	SCOTOPIC	COLOR TEMP (CCT)	CRI	RATED LIFE (L70)	INPUT VOLTAGE	INPUT FREQUENCY
SL-MS-40HPLED	40W	4,286	7,072	5000K	70+	>200,000	120~277V	50/60Hz
SL-MS-50HPLED	50W	5,360	8,844	5000K	70+	>200,000	120~277V	50/60Hz
SL-MS-60HPLED	60W	6,432	10,613	5000K	70+	>200,000	120~277V	50/60Hz

Ordering Guide

Example: SL-MS-50HPLED-50-MV-BZ-3-PC

SL-MS

MODEL	WATTS	COLOR TEMP	VOLTAGE	FINISH	MOUNTING	OPTIONS
SL-MS	40W-40HPLED	30-3000K	MV=120-277V	<u>STANDARD:</u>	(3) 3" ROUND POST FITTER (4) 4" ROUND POST FITTER (5) 2/8" ROUND POST FITTER	PC-BUTTON PHOTO CELL
	50W-50HPLED	40-4000K		BZ- BRONZE		HSS-HOUSE SIDE SHIELD
	60W-60HPLED	50-5000K		<u>ADDITIONAL CHARGE:</u> GRY-GRAY BLK-BLACK WH- WHITE CUS-CUSTOM		WC-WIRELESS CONTROLS MG-MARINE GRADE FINISH FAL-FROSTED ACRYLIC LENS

Dimensions

