



DATE	
PROJECT	
TYPE	
NOTE	
PREPARED BY	

VL-012

LED Canopy Light



The **VL-012** ensures strong luminosity and durability. A few ideal locations for the **VL-012** are: hallways, entrances, underpasses and parking garages. This fixture suits any location due to its availability in two different sizes. The **VL-012** offers competitive pricing and includes a 3 year warranty.

FEATURES

- Starting Temperature: -40°C
- UL & CUL listed for wet locations
- Suitable for wet locations
- 5000K
- Driver: Constant current, 120~277V
- Operating life: >100,000 hours
- 3 year warranty



CONSTRUCTION

- Solid construction die-cast aluminum body
- UV stabilized powder coat bronze finish (standard)
- High-impact acrylic diffuser

MODEL #	INPUT POWER	LUMEN OUTPUT	SCOTOPIC	COLOR TEMP (CCT)	CRI	RATED LIFE (L70)	INPUT VOLTAGE	INPUT FREQUENCY
VL-012-38LED	38W	4,356	7,187	5000K	70+	>100,000	120 ~ 277V	50/60Hz
VL-012-55LED	55W	5,276	8,705	5000K	70+	>100,000	120 ~ 277V	50/60Hz

Ordering Guide

Example: VL-012-38LED-50-MV-BZ-SM

VL-012					
MODEL	WATTS	COLOR TEMP	VOLTAGE	FINISH	MOUNTING
VL-012	38W-38LED 55W-55LED	50-5000K	MV=120~277V	BZ-BRONZE	SM-SURFACE MOUNT

Dimensions

