



DATE	
PROJECT	
TYPE	
NOTE	
PREPARED BY	

## VL-023

## LED Canopy Light



The **VL-023** ensures strong luminosity and durability. A few ideal locations for the **VL-023** are: hallways, entrances, underpasses and parking garages. The quick mount structure delivers easy installation for contractors. The **VL-023** offers competitive pricing and includes a 3 year warranty.

### FEATURES

- Starting Temperature: -40°C
- UL & CUL listed for wet locations
- Suitable for wet locations
- 5000K
- Driver: Constant current, 120~277V
- Operating life: >100,000 hours
- 3 year warranty



### CONSTRUCTION

- Solid construction die-cast aluminum body
- UV stabilized powder coat bronze finish (standard)
- Prismatic lens for uniform light distribution

MODEL #	INPUT POWER	LUMEN OUTPUT	SCOTOPIC	COLOR TEMP (CCT)	CRI	RATED LIFE (L70)	INPUT VOLTAGE	INPUT FREQUENCY
VL-023-68LED	68W	6,429	10,608	5000K	70+	>100,000	120 ~ 277V	50/60Hz

## Ordering Guide

Example: VL-023-68LED-50-MV-WH-QM

MODEL	WATTS	COLOR TEMP	VOLTAGE	FINISH	MOUNTING
VL-023	68W-68LED	50-5000K	MV=120~277V	WH-WHITE	QM-QUICK MOUNT

# Dimensions

