



DATE	
PROJECT	
TYPE	
NOTE	
PREPARED BY	

VL-1571PM-ONE

LED Architectural Floodlight



The energy efficient LED light fixture, **VL-1571PM-ONE** provides savings to customers by adding the optional built-in photo sensor that automatically activates lighting at night and turns off lighting during daytime. It is ideal for locations such as parking areas, entrances, walkways, underpasses and roadways. The multifunctional **VL-1571PM-ONE** can be installed with various mounting methods. The **VL-1571PM-ONE** offers competitive pricing and includes a 5 year warranty.

FEATURES

- Starting Temperature: -40°C
- UL & CUL listed for wet locations
- Driver: Constant current, 120-277v
- Operating life: >50,000 hours
- 5 year warranty

OPTIONS

- (PC) Photo control
- (PM) Pole mount
- (SB) Swivel bracket
- (SF) Slip fitter
- (SFS) SFS bracket

CONSTRUCTION

- Solid construction die-cast aluminum body
- UV stabilized powder coat finish
- Powder coat bronze finish (standard)



MODEL #	INPUT POWER	LUMEN OUTPUT	SCOTOPIC	COLOR TEMP (CCT)	CRI	RATED LIFE (L70)	INPUT VOLTAGE	INPUT FREQUENCY	HID EQUIVALENT
VL-1571PM-ONE-21LED	22W	1,825	3,011	5000K	70+	>50,000	120-277v	50/60Hz	100w MH
VL-1571PM-ONE-53LED	52W	3,846	6,346	5000K	70+	>50,000	120-277v	50/60Hz	250w MH

Ordering Guide

Example: VL-1571PM-ONE-53LED-50-MV-BZ-PC

MODEL	WATTS	COLOR TEMP	VOLTAGE	FINISH	OPTIONS
VL-1571PM-ONE	21W-21LED 53W-53LED	50-5000K	MV=120-277V	BZ- BRONZE	PC-PHOTO CONTROL PM-POLE MOUNT SB-WIVEL BRACKET SF-SLIP FITTER SFS-SFS BRACKET

Dimensions

