



DATE	
PROJECT	
TYPE	
NOTE	
PREPARED BY	

**VL-1571SFB**

**LED Floodlight**



The energy efficient LED light fixture, **VL-1571SFB** provides savings to customers by adding the optional built-in photo sensor that automatically activates lighting at night and turns off lighting during daytime. It is ideal for locations such as parking areas, entrances, walkways, underpasses and roadways. The **VL-1571SFB** offers competitive pricing and includes a 3 year warranty.

**FEATURES**

- Starting Temperature: -40°C
- CRI: 70+
- UL & CUL listed for wet locations
- Driver: Constant current, 120-277V
- Operating life: >50,000 hours

**CONSTRUCTION**

- Solid construction die-cast aluminum body
- UV stabilized powder coat finish
- Powder coat bronze finish (standard)

**OPTIONS**

- (PC) Photo control
- (SF) Slip fitter



PHOTO CONTROL



SLIP FITTER

MODEL #	INPUT POWER	LUMEN OUTPUT	SCOTOPIC	COLOR TEMP (CCT)	CRI	RATED LIFE (L70)	INPUT VOLTAGE	INPUT FREQUENCY	HID EQUIVALENT
VL-1571SFB-50LED	50W	3,846	6,346	4700K	70+	>50,000	120-277V	50/60Hz	150w-175w MH

# Ordering Guide

Example: VL-1575SFB-50LED-47-MV-BZ-PC

MODEL	WATTS	COLOR TEMP	VOLTAGE	FINISH	OPTIONS
VL-1575SFB	50W-50LED	47-47000K	MV=120-277V	BZ- BRONZE	<u>Add'l Cost:</u> (PC) PHOTO CONTROL (SF) SLIP FITTER

# Dimensions

