



DATE	
PROJECT	
TYPE	
NOTE	
PREPARED BY	

VL-1571SFS-ONE

LED Architectural Floodlight



The energy efficient LED light fixture, **VL-1571SFS-ONE** provides savings to customers by adding the optional built-in photo sensor that automatically activates lighting at night and turns off lighting during daytime. It is ideal for locations such as parking areas, entrances, walkways, underpasses and roadways. The multifunctional **VL-1571SFS-ONE** can be installed with a swivel bracket or slip-fitter. The **VL-1571SFS-ONE** offers competitive pricing and includes a 5 year warranty.

FEATURES

- Starting Temperature: -40°C
- UL & CUL listed for wet locations
- Driver: Constant current, 120-277v
- Operating life: >50,000 hours
- 5 year warranty

OPTIONS

- (JB) Junction box
- (PC) Photo control
- (SB) Swivel bracket
- (SF) Slip fitter

CONSTRUCTION

- Solid construction die-cast aluminum body
- UV stabilized powder coat finish
- Powder coat bronze finish (standard)



JUNCTION BOX



SLIP FITTER



PHOTO CONTROL



SWIVEL BRACKET

MODEL #	INPUT POWER	LUMEN OUTPUT	SCOTOPIC	COLOR TEMP (CCT)	CRI	RATED LIFE (L70)	INPUT VOLTAGE	INPUT FREQUENCY	HID EQUIVALENT
VL-1571SFS-ONE	50W	3,846	6,346	5000K	70+	>50,000	120-277v	50/60Hz	150w-175w MH

Ordering Guide

Example: VL-1571SFS-ONE-50LED-50-MV-BZ-PC

MODEL	WATTS	COLOR TEMP	VOLTAGE	FINISH	OPTIONS
VL-1571SFS-ONE	50W-50LED	50-5000K	MV=120-277V	BZ- BRONZE	PC-PHOTO CONTROL SF-SLIP FITTER SB-WIVEL BRACKET

Dimensions

