



DATE	
PROJECT	
TYPE	
NOTE	
PREPARED BY	

VL-1860

LED Floodlight



The **VL-1860** provides powerful luminosity while keeping the LED's at a moderate temperature. It has been designed to fit in various locations such as: parking areas, entrances, walkways, underpasses and roadways. This fixture is multifunctional due to the various mounting options. The **VL-1860** offers competitive pricing and includes a 3 year warranty.

FEATURES

- Starting Temperature: -40°C
- CRI: 70+
- Color temp: 4000K (add'l cost), 5000K (standard)
- UL listed for wet locations
- Driver: Constant current, 120~277V
- Operating life: >50,000 hours
- 5 year warranty

CONSTRUCTION

- Solid construction die-cast aluminum body
- Bronze or black finish (standard)
- Tempered glass

OPTIONS

- (PC) Photo control
- (PM) Pole mount
- (SF) Slip fitter
- (SB) Swivel bracket
- (SFS) SFS bracket



PHOTO CONTROL



SLIP FITTER



SWIVEL BRACKET



POLE MOUNT



SFS BRACKET

MODEL #	INPUT POWER	LUMEN OUTPUT	COLOR TEMP (CCT)	CRI	RATED LIFE (L70)	INPUT VOLTAGE	INPUT FREQUENCY	HID EQUIVALENT
VL-1860-21LED	21W	2,169	5000K	70+	>50,000	120~277V	50/60Hz	100w MH
VL-1860-32LED	32W	2,788	5000K	70+	>50,000	120~277V	50/60Hz	100W-150W MH
VL-1860-42LED	42W	3,908	5000K	70+	>50,000	120~277V	50/60Hz	200w MH

Ordering Guide

Example: VL-1860-21LED-50-MV-BZ-PC

VL-1860					
MODEL	WATTS	COLOR TEMP	VOLTAGE	FINISH	OPTIONS
VL-1860	21W-21LED 32W-32LED 42W-42LED	<u>ADD'L COST:</u> 40-4000K <u>STANDARD:</u> 50-5000K	MV—120~277V	BZ— BRONZE	<u>ADD'L COST:</u> (PC) PHOTO CONTROL (PM) POLE MOUNT (SF) SLIP FITTER (SB) SWIVEL BRACKET (SFS) SFS BRACKET

Dimensions

