



DATE	
PROJECT	
TYPE	
NOTE	
PREPARED BY	

VL-206

LED Floodlight



The **VL-206** is built with a high efficient LED engine that ensures durability and strong luminosity. It is ideal for locations such as parking areas, entrances, walkways, underpasses and roadways. The multifunctional **VL-206** can be installed with various mounting methods. The **VL-206** offers competitive pricing and includes a 5 year warranty.

FEATURES

- Starting Temperature: -40°C
- UL & CUL listed for wet locations
- Driver: Constant current, 120-277v
- Operating life: >50,000 hours
- 5 year warranty

CONSTRUCTION

- Solid construction die-cast aluminum body
- UV stabilized powder coat finish
- Powder coat bronze finish (standard)

OPTIONS

- (PC) Photo control
- (SF) Slip fitter
- (SB) Swivel bracket



MODEL #	INPUT POWER	LUMEN OUTPUT	SCOTOPIC	COLOR TEMP (CCT)	CRI	RATED LIFE (L70)	INPUT VOLTAGE	INPUT FREQUENCY	HID EQUIVALENT
VL-206-42LED	42W	3,536	5,834	5000K	70+	>50,000	120-277v	50/60Hz	175w MH

Ordering Guide

Example: VL-206-42LED-50-MV-BZ-PC

MODEL	WATTS	COLOR TEMP	VOLTAGE	FINISH	OPTIONS
VL-206	42W-42LED	50-5000K	MV=120-277V	BZ- BRONZE	(PC) PHOTO CONTROL (SF) SLIP FITTER (SB) SWIVEL BRACKET

Dimensions

