



DATE	
PROJECT	
TYPE	
NOTE	
PREPARED BY	

VL-2080

LED Floodlight



The **VL-2080** ensures powerful luminosity and provides security for any given location. It is constructed with robust die cast aluminum and given a tempered glass lens. The multifunctional, **VL-2080** operates as a floodlight or an area light due to various mounting options. The **VL-2080** offers competitive pricing and includes a 5 year warranty.

FEATURES

- Starting Temperature: -40°C
- UL listed for wet locations
- CRI: 70+
- Color temp: 5000K
- Driver: Constant current, 120~277V, 347V** (optional)
- Operating life: >50,000 hours
- 5 year warranty

OPTIONS

- PC—Photo Control
- SP—Surge Protection
- YM—Yoke Mount
- SB—Swivel Bracket

CONSTRUCTION

- Die-cast aluminum body
- Bronze finish (standard); other finishes available** (custom)
- Tempered glass lens

MODEL #	INPUT POWER	LUMEN OUTPUT	COLOR TEMP (CCT)	CRI	RATED LIFE (L70)	INPUT VOLTAGE	INPUT FREQUENCY	EQUIVALENT
VL-2080-336LED	336W	40,675	5000K	70+	>100,000	120~277V	50/60Hz	100W MH
VL-2080-408LED	408W	48,501	5000K	70+	>100,000	120~277V	50/60Hz	1500W MH

Ordering Guide

Example: VL-2080-336LED-50-MV-BZ-PC

VL-2080					
MODEL	WATTS	COLOR TEMP	VOLTAGE	FINISH	OPTIONS**
VL-2080	336W-336LED	50-5000K	MV—120~277V	BZ-BRONZE	PC—PHOTO CONTROL
	408W-408LED		347V**	CUS-CUSTOM**	SP—SURGE PROTECTION YM—YOKE MOUNT SB—SWIVEL BRACKET

Dimensions

