



DATE	
PROJECT	
TYPE	
NOTE	
PREPARED BY	

SM/LG-VL-2227

LED Interior Ceiling Mount



The **VL-2227** displays a simple yet sophisticated look. This fixture is ideal for ceiling and wall mount applications; some locations include: residential, institutional, and multifamily locations. Compared to fluorescent lights, the **VL-2227** is more energy efficient, durable, and low maintenance. This fixture works best in dry locations. The **VL-2227** fixture offers competitive pricing and includes a 3 year warranty.

FEATURES

- Starting Temperature: -30°C ~ 60°C
- Suitable for dry locations
- 4000K
- 120V
- Operating life: >50,000 hours
- 3 year warranty



CONSTRUCTION

- Steel housing
- White diffuser
- Nickel finish (standard)

MODEL #	INPUT POWER	LUMEN OUTPUT	SCOTOPIC	COLOR TEMP (CCT)	CRI	RATED LIFE (L70)	INPUT VOLTAGE	INPUT FREQUENCY
SM-VL-2227-14LED	14W	1,200	1,980	4000K	80	>50,000	120V	50/60 Hz
LG-VL-2227-20LED	20W	1,660	2,739	4000K	80	>50,000	120V	50/60 Hz

Ordering Guide

Example: LG-VL-2227-20LED-40-120V-NIC

SM/LG-VL-2227

MODEL	WATTS	COLOR TEMP	VOLTAGE	FINISH
SM-VL-2227-14LED	14W-14LED	40-4000K	120V	NIC-NICKEL
LG-VL-2227-20LED	20W-20LED	40-4000K	120V	NIC-NICKEL

Dimensions

SM-VL-2227-14LED



LG-VL-2227-20LED

