



DATE	
PROJECT	
TYPE	
NOTE	
PREPARED BY	

VL-367

LED Canopy Light



The **VL-367** ensures strong luminosity and durability. A few ideal locations for the **VL-367** are: hallways, entrances, underpasses and parking garages. The quick mount structure delivers easy installation for contractors. The **VL-367** offers competitive pricing and includes a 5 year warranty.

FEATURES

- Starting Temperature: -40°C
- UL & CUL listed for wet locations
- Suitable for wet locations
- 5000K
- Driver: Constant current, 120~277V
- Operating life: >100,000 hours
- 5 year warranty



CONSTRUCTION

- Solid construction die-cast aluminum body
- UV stabilized powder coat bronze finish (standard)
- Unique quick mount design

MODEL #	INPUT POWER	LUMEN OUTPUT	SCOTOPIC	COLOR TEMP (CCT)	CRI	RATED LIFE (L70)	INPUT VOLTAGE	INPUT FREQUENCY
VL-367-40LED	40W	3,843	6,341	5000K	70+	>100,000	120 ~ 277V	50/60 Hz
VL-367-59LED	59W	5,771	9,522	5000K	70+	>100,000	120 ~ 277V	50/60 Hz

Ordering Guide

Example: VL-367-59LED-50-MV-BZ-QM

VL-367

MODEL	WATTS	COLOR TEMP	VOLTAGE	FINISH	MOUNTING
VL-367	40W-40LED 59W-59LED	50-5000K	MV=120-277V	STANDARD: BZ-BRONZE WH-WHITE	PC-PHOTO CONTROL QM-QUICK MOUNT

Dimensions

