



DATE	
PROJECT	
TYPE	
NOTE	
PREPARED BY	

## VL-368

## LED Canopy Light



The **VL-368** ensures strong luminosity and durability. A few ideal locations for the **VL-368** are: gas stations, high ceilings and parking garages. The quick mount structure delivers easy installation for contractors. The **VL-368** offers competitive pricing and includes a 3 year warranty.

### FEATURES

- Starting Temperature: -40°C
- UL & CUL listed for wet locations
- Suitable for wet locations
- 5000K
- Driver: Constant current, 120~277V
- Operating life: >100,000 hours
- 3 year warranty



### CONSTRUCTION

- Solid construction die-cast aluminum body
- UV stabilized powder coat bronze finish (standard)
- Heat and impact resistant tempered glass

MODEL #	INPUT POWER	LUMEN OUTPUT	SCOTOPIC	COLOR TEMP (CCT)	CRI	RATED LIFE (L70)	INPUT VOLTAGE	INPUT FREQUENCY
VL-368-99LED	99W	12,560	20,724	5000K	70+	>100,000	120 ~ 277V	50/60 Hz
VL-368-130LED	130W	15,362	25,347	5000K	70+	>100,000	120 ~ 277V	50/60 Hz
VL-368-165LED	165W	21,120	34,848	5000K	70+	>100,000	120 ~ 277V	50/60 Hz
VL-368-186LED	186W	19,246	31,756	5000K	70+	>100,000	120 ~ 277V	50/60 Hz

## Ordering Guide

Example: VL-368-99LED-50-MV-WH-QM

MODEL	WATTS	COLOR TEMP	VOLTAGE	FINISH	MOUNTING
VL-368	99W-99LED 130W-130LED 165W-165LED 186W-186LED	50-5000K	MV=120-277V	WH-WHITE	QM-QUICK MOUNT

Crystal Lighting Corporation - 13182 Flores St., Santa Fe Springs, Ca. 90670

Phone: 562-944-0223 - Fax: 562-944-0225 - WEB: [www.crystallighting.us](http://www.crystallighting.us)

Crystal Lighting is BUY AMERICAN compliant - All products are proudly manufactured and/or assembled in the USA

# Dimensions

