



DATE	
PROJECT	
TYPE	
NOTE	
PREPARED BY	

VL-560-L2

LED Floodlight



The VL-560-L2 provides powerful luminosity while keeping the LED's at a moderate temperature. It has been designed to fit in various locations such as: parking areas, entrances, walkways, underpasses and roadways. This fixture is multifunctional and can be used as a floodlight or an area light. The VL-5602-L2 offers competitive pricing and includes a 3 year warranty.

FEATURES

- Starting Temperature: -40°C
- CRI: 70+
- UL & CUL listed for wet locations
- Driver: Constant current, 120-277V
- Operating life: >50,000 hours

CONSTRUCTION

- Solid construction die-cast aluminum body
- UV stabilized powder coat finish
- Powder coat bronze finish (standard)
- Heat and impact resistant tempered glass

OPTIONS

- (PC) Photo control
- (PM) Pole mount
- (SF) Slip fitter
- (SB) Swivel bracket



PHOTO CONTROL



SLIP FITTER



SWIVEL BRACKET



POLE MOUNT

MODEL #	INPUT POWER	LUMEN OUTPUT	SCOTOPIC	COLOR TEMP (CCT)	CRI	RATED LIFE (L70)	INPUT VOLTAGE	INPUT FREQUENCY	HID EQUIVALENT
VL-560-L2-80LED	80W	8,795	14,512	5000K	70+	>50,000	120-277V	50/60Hz	250w MH

Ordering Guide

Example: VL-560-L2-80LED-50-MV-BZ-PC

MODEL	WATTS	COLOR TEMP	VOLTAGE	FINISH	OPTIONS
VL-560-L2	80W-80LED	50-5000K	MV=120-277V	BZ- BRONZE	<u>Add'l Cost:</u> (PC) PHOTO CONTROL (PM) POLE MOUNT (SF) SLIP FITTER (SB) SWIVEL BRACKET

Dimensions

