



| | |
|-------------|--|
| DATE | |
| PROJECT | |
| TYPE | |
| NOTE | |
| PREPARED BY | |

VL-560-T3

LED Architectural Floodlight

The VL-560-T3 has built-in heat sinks that ensure efficiency and strong luminosity. It is ideal for locations such as parking areas, entrances, walkways, underpasses and roadways. The multifunctional VL-560-T3 can be installed with various mounting methods. The VL-560-T3 offers competitive pricing and includes a 5 year warranty.



FEATURES

- Starting Temperature: -40°C
- UL & CUL listed for wet locations
- Driver: Constant current, 120-277v
- Operating life: >50,000 hours
- 5 year warranty

CONSTRUCTION

- Solid construction die-cast aluminum body
- UV stabilized powder coat finish
- Heat and impact resistant tempered glass
- Powder coat bronze finish (standard)

OPTIONS

- (DIMM) Dimmable
- (FHC) Front hinged cover
- (PC) Photo control
- (PM) Pole mount
- (SF) Slip fitter
- (SB) Swivel bracket



| MODEL # | INPUT POWER | LUMEN OUTPUT | SCOTOPIC | COLOR TEMP (CCT) | CRI | RATED LIFE (L70) | INPUT VOLTAGE | INPUT FREQUENCY | HID EQUIVALENT |
|------------------|-------------|--------------|----------|------------------|-----|------------------|---------------|-----------------|----------------|
| VL-560-T3-113LED | 113W | 9,518 | 15,705 | 5000K | 70+ | >50,000 | 120-277v | 50/60Hz | 250w MH |
| VL-560-T3-188LED | 188W | 19,739 | 32,570 | 5000K | 70+ | >50,000 | 120-277v | 50/60Hz | 400w MH |

Ordering Guide

Example: VL-560-T3-188LED-50-MV-BZ-PC

| MODEL | WATTS | COLOR TEMP | VOLTAGE | FINISH | OPTIONS |
|-----------|----------------------------|------------|-------------|------------|---|
| VL-560-T3 | 113W-113LED 188W-188LED | 50-5000K | MV=120-277V | BZ- BRONZE | (DIMM) DIMMABLE (FHC) FRONT HINGED COVER (PC) PHOTO CONTROL (PM) POLE MOUNT (SF) SLIP FITTER (SB) SWIVEL BRACKET |

Dimensions

