



DATE	
PROJECT	
TYPE	
NOTE	
PREPARED BY	

**VL-757-U2**

**LED Floodlight**



The VL-757-U2 provides powerful luminosity and efficiency. It has been designed to fit in various locations such as: parking areas, entrances, walkways, underpasses and roadways. This fixture is multifunctional and can be used as a floodlight or an area light. The VL-757-U2 offers competitive pricing and includes a 3 year warranty.

**FEATURES**

- Starting Temperature: -40°C
- CRI: 70+
- UL & CUL listed for wet locations
- Driver: Constant current, 120-277V
- Operating life: >50,000 hours

**CONSTRUCTION**

- Solid construction die-cast aluminum body
- UV stabilized powder coat finish
- Powder coat bronze finish (standard)
- Front hinged door frame

**OPTIONS**

- (PC) Photo control
- (SF) Slip fitter
- (SB) Swivel bracket



PHOTO CONTROL



SLIP FITTER



SWIVEL BRACKET



POLE MOUNT

MODEL #	INPUT POWER	LUMEN OUTPUT	SCOTOPIC	COLOR TEMP (CCT)	CRI	RATED LIFE (L70)	INPUT VOLTAGE	INPUT FREQUENCY	HID EQUIVALENT
VL-757-U2-60LED	60W	6,659	10,987	5000K	70+	>50,000	120-277V	50/60Hz	200w MH
VL-757-U2-82LED	82W	8,121	13,399	5000K	70+	>50,000	120-277V	50/60Hz	200w MH
VL-757-U2-112LED	112W	10,692	17,642	5000K	70+	>50,000	120-277V	50/60Hz	250w MH

Crystal Lighting Corporation - 13182 Flores St., Santa Fe Springs, Ca. 90670

Phone: 562-944-0223 - Fax: 562-944-0225 - WEB: [www.crystallighting.us](http://www.crystallighting.us)

Crystal Lighting is BUY AMERICAN compliant - All products are proudly manufactured and/or assembled in the USA

# Ordering Guide

Example: VL-757-U2-82LED-50-MV-BZ-PC

MODEL	WATTS	COLOR TEMP	VOLTAGE	FINISH	OPTIONS
VL-757-U2	60W-60LED 82W-82LED 112W-112LED	50-5000K	MV=120-277V	BZ- BRONZE	<u>Add'l Cost:</u> (PC) PHOTO CONTROL (SF) SLIP FITTER (SB) SWIVEL BRACKET

## Dimensions

