



DATE	
PROJECT	
TYPE	
NOTE	
PREPARED BY	

VL-787

LED Floodlight



The **VL-787** is a versatile and powerful light fixture. It has been designed to fit in various locations such as: parking areas, entrances, walkways, underpasses and roadways. It is multifunctional and can be installed with a slip fitter or a swivel bracket. The **VL-787** offers competitive pricing and includes a 3 year warranty.

FEATURES

- Starting Temperature: -40°C
- CRI: 70+
- UL & CUL listed for wet locations
- Driver: Constant current, 120-277V, 347V (add'l cost)
- Operating life: >50,000 hours

CONSTRUCTION

- Solid construction die-cast aluminum body
- Corrosion resistant hardware
- UV stabilized powder coat finish
- Powder coat bronze finish (standard)

OPTIONS

- (PC) Photo control
- (SF) Slip fitter
- (SP) Surge protector
- (SB) Swivel bracket



PHOTO CONTROL



SLIP FITTER



SWIVEL BRACKET

MODEL #	INPUT POWER	LUMEN OUTPUT	SCOTOPIC	COLOR TEMP (CCT)	CRI	RATED LIFE (L70)	INPUT VOLTAGE	INPUT FREQUENCY	HID EQUIVALENT
VL-787-138LED	138W	16,900	27,885	5000K	70+	>50,000	120-277V	50/60Hz	250w MH
VL-787-187LED	187W	25,350	41,828	5000K	70+	>50,000	120-277V	50/60Hz	400w MH
VL-787-256LED	256W	34,857	57,514	5000K	70+	>50,000	120-277V	50/60Hz	400-600w MH

Ordering Guide

Example: VL-787-187LED-50-MV-BZ-PC

VL-787					
MODEL	WATTS	COLOR TEMP	VOLTAGE	FINISH	OPTIONS
VL-787	138W-138LED 187W-187LED 256W-256LED	50-5000K	MV=120-277V	BZ- BRONZE	<u>Add'l Cost:</u> (PC) Photo control (SF) Slip fitter (SP) Surge protector (SB) Swivel bracket

Dimensions

