



DATE	
PROJECT	
TYPE	
NOTE	
PREPARED BY	

VL-8160-5

LED Floodlight

The versatile **VL-8160-5** provides strong luminosity with minimum power. The centerpiece of this fixture is designed to maximize heat dissipation from the light engine. This design helps the fixture run cooler while increasing the operating life. To add to these features, the **VL-8160-5** offers competitive pricing and includes a 3 year warranty.



FEATURES

- Starting Temperature: -40°C
- CRI: 70+
- UL & CUL listed for wet locations
- Driver: Constant current, 120-277V, 347V (w/ adder)
- Operating life: >50,000 hours

CONSTRUCTION

- Solid construction die-cast aluminum body
- UV stabilized powder coat finish
- Powder coat bronze finish (standard)
- Corrosion resistant hardware

OPTIONS

- (PC) Photo control
- (SF) Slip fitter
- (SB) Swivel bracket



PHOTO CONTROL



SLIP FITTER



SWIVEL BRACKET

MODEL #	INPUT POWER	LUMEN OUTPUT	SCOTOPIC	COLOR TEMP (CCT)	CRI	RATED LIFE (L70)	INPUT VOLTAGE	INPUT FREQUENCY	HID EQUIVALENT
VL-8160-5-196LED	196W	22,036	36,359	5000K	70+	>50,000	120-277V	50/60Hz	400w MH

Ordering Guide

Example: VL-8160-5-196LED-50-MV-BZ-PC

MODEL	WATTS	COLOR TEMP	VOLTAGE	FINISH	OPTIONS
VL-8160-5	196W-196LED	50-5000K	MV=120-277V 347V (w/ adder)	BZ- BRONZE	<u>Add'l Cost:</u> (PC) PHOTO CONTROL (SF) SLIP FITTER (SB) SWIVEL BRACKET

Dimensions

