



DATE	
PROJECT	
TYPE	
NOTE	
PREPARED BY	

VL-CH01-T3/T5

LED Roadway Light

The **VL-CH01** ensures strong luminosity from dusk to dawn. By occupying a single source LED, the **VL-CH01** provides prismatic-designed light output in any given location. Other than roadways, the **VL-CH01** is also ideal for: roadways, parking areas, and walkways. This fixture offers competitive pricing and includes a 3 year warranty.



FEATURES

- Starting Temperature: -40°C
- UL & CUL listed for wet locations
- 5000K
- Driver: Constant current, 120~277V/120V
- Operating life: >100,000 hours
- 3 year warranty



CONSTRUCTION

- Solid construction die-cast aluminum body
- UV stabilized powder coat bronze finish (standard)

MODEL #	INPUT POWER	LUMEN OUTPUT	SCOTOPIC	COLOR TEMP (CCT)	CRI	RATED LIFE (L70)	INPUT VOLTAGE	INPUT FREQUENCY
VL-CH01-T3-34LED	34W	3,675	6,064	5000K	70+	>100,000	120 ~ 277V	50/60 Hz
VL-CH01-T3-51LED	51W	6,432	10,613	5000K	70+	>100,000	120 ~ 277V	50/60 Hz
VL-CH01-T5-35LED	35W	3,165	5,222	5000K	70+	>100,000	120V	50/60 Hz
VL-CH01-T5-57LED	57W	4,977	8,212	5000K	70+	>100,000	120 ~ 277V	50/60 Hz

Ordering Guide

Example: VL-CH01-51LED-T3-50-MV-GR

MODEL	WATTS	DISTRIBUTION	COLOR TEMP	VOLTAGE	FINISH
VL-CH01	34W-34LED 51W-51LED	T3	50-5000K	MV=120~277V	GR-GRAY
VL-CH01	35W-35LED 57W-57LED	T5		120V	

Dimensions

