



DATE	
PROJECT	
TYPE	
NOTE	
PREPARED BY	

VL-LBSS

LED Canopy Light



The VL-LBSS ensures strong luminosity. It displays a low profile appearance while providing safety and durability. A few ideal locations for the VL-LBSS are: hallways, entrances, underpasses and parking garages. The VL-LBSS offers competitive pricing and includes a 3 year warranty.

FEATURES

- Starting Temperature: 34°C ~ 54°C
- UL & CUL listed for wet locations
- DLC listed
- Suitable for wet locations
- Driver: Constant current, 120V
- Operating life: >50,000 hours



CONSTRUCTION

- Solid construction die-cast aluminum body
- Polycarbonate lens
- Powder coat black finish (standard)

MODEL #	INPUT POWER	LUMEN OUTPUT	SCOTOPIC	COLOR TEMP (CCT)	CRI	RATED LIFE (L70)	INPUT VOLTAGE	INPUT FREQUENCY
VL-LBSS-28LED	28W	2,800	4,620	5000K	80+	>50,000	120 ~ 277V	50/60Hz
VL-LBSS-40LED	40W	4,000	6,600	5000K	80+	>50,000	120 ~ 277V	50/60Hz
VL-LBSS-60LED	60W	6,000	9,900	5000K	80+	>50,000	120 ~ 277V	50/60Hz
VL-LBSS-90LED	90W	9,000	14,850	5000K	80+	>50,000	120 ~ 277V	50/60Hz

Ordering Guide

Example: VL-LBSS-60LED-50-MV-BLK

VL-LBSS	WATTS	COLOR TEMP	VOLTAGE	FINISH
MODEL				
VL-LBSS	28W-28LED 40W-40LED 60W-60LED 90W-90LED	50-5000K	MV=120-277V	BLK-BLACK