



DATE	
PROJECT	
TYPE	
NOTE	
PREPARED BY	

## VL-LH1671

## LED Linear Highbay



The **VL-LH1671** ensures strong luminosity and durability. Available in four different wattages, the **VL-LH1671** is ideal for locations such as: warehouses, parking garages, shops, and other commercial locations. The **VL-LH1671** offers competitive pricing and includes a 5 year warranty.

### FEATURES

- Starting Temperature: -20 ~ 45°C
- UL & CUL listed for wet locations
- IP20
- 4000K & 5000K (check wattage info below for availability)
- Driver: Constant current, 120~277V
- Operating life: >50,000 hours
- 5 year warranty



### CONSTRUCTION

- Steel housing, clear polycarbonate lens
- white finish (standard)
- Pendant mounting

MODEL #	INPUT POWER	LUMEN OUTPUT	SCOTOPIC	COLOR TEMP (CCT)	CRI	RATED LIFE (L70)	INPUT VOLTAGE	INPUT FREQUENCY	DIMENSIONS
VL-LH1671-105LED	105W	13,650	22,522	4000K/5000K	80	>50,000	120 ~ 277V	50/60Hz	23.6" x 12.6" x 3.5"
VL-LH1671-165LED	165W	21,450	35,393	4000K/5000K	80	>50,000	120 ~ 277V	50/60Hz	23.6" x 17.3" x 3.5"
VL-LH1671-220LED	220W	28,600	47,190	5000K	80	>50,000	120 ~ 277V	50/60Hz	45.9" x 12.6" x 3.5"

## Ordering Guide

Example: VL-LH1671-165LED-50-MV-WH

VL-LH1671				
MODEL	WATTS	COLOR TEMP	VOLTAGE	FINISH
VL-LH1671	105W-105LED	40-4000K (only for 105W & 165W)	120-277V	WH-WHITE
	165W-165LED	50-5000K		
	220W-220LED			