



DATE	
PROJECT	
TYPE	
NOTE	
PREPARED BY	

VL-LH1671

LED Linear Highbay



The **VL-LH1671** ensures strong luminosity and durability. Available in four different wattages, the **VL-LH1671** is ideal for locations such as: warehouses, parking garages, shops, and other commercial locations. The **VL-LH1671** offers competitive pricing and includes a 3 year warranty.

FEATURES

- Starting Temperature: -20 ~ 45°C
- UL & CUL listed for wet locations
- IP20
- 5000K
- Driver: Constant current, 120~277V
- Operating life: >50,000 hours
- 3 year warranty

CONSTRUCTION

- Steel housing, clear polycarbonate lens
- white finish (standard)
- Pendant mounting



MODEL #	INPUT POWER	LUMEN OUTPUT	SCOTOPIC	COLOR TEMP (CCT)	CRI	RATED LIFE (L70)	INPUT VOLTAGE	INPUT FREQUENCY	DIMENSIONS
VL-LH1671-105LED	105W	13,650	22,522	5000K	80	>50,000	120 ~ 277V	50/60Hz	23.6" x 12.6" x 3.5"
VL-LH1671-165LED	165W	21,450	35,393	5000K	80	>50,000	120 ~ 277V	50/60Hz	23.6" x 17.3" x 3.5"
VL-LH1671-220LED	220W	28,600	47,190	5000K	80	>50,000	120 ~ 277V	50/60Hz	45.9" x 12.6" x 3.5"

Ordering Guide

Example: VL-LH1671-165LED-50-120~277V-BZ

VL-LH1671

MODEL	WATTS	COLOR TEMP	VOLTAGE	FINISH
VL-LH1671	105W-105LED	50-5000K	120~277V	WH-WHITE
	165W-165LED			
	220W-220LED			