



DATE	
PROJECT	
TYPE	
NOTE	
PREPARED BY	

VL-LH1671

LED Linear High Bay



The VL-LH1671 ensures strong luminosity and durability. Available in three different wattages currently. It is ideal for locations such as: warehouses, parking garages, shops and other commercial spaces. The VL-LH1671 offers competitive pricing and includes a 5 year warranty.

FEATURES

- Starting Temperature: -20 ~ 45°C
- UL & CUL listed for wet locations
- IP rating: IP20
- 4000k & 5000k (check wattage info below for availability)
- Driver: Constant current, 120-277V
- Operating life: >50,000 hours
- 5 year warranty

CONSTRUCTION

- Steel Housing, frosted Acrylic lens
- Powder coat white finish (standard)
- Pendant Mounting Hardware available (optional)



MODEL #	INPUT POWER	LUMEN OUTPUT	LPW	COLOR TEMP (CCT)	CRI	RATED LIFE (L70)	INPUT VOLTAGE	INPUT FREQUENCY	DIMENSIONS
VL-LH1671-105LED	105W	13,650	130	4000/5000K	80+	>50,000	120-277V	50/60Hz	23.6" X 12.6" X 3.5"
VL-LH1671-165LED	165W	21,450	130	4000/5000K	80+	>50,000	120-277V	50/60Hz	23.6" X 12.6" X 3.5"
VL-LH1671-220LED	220W	28,600	130	5000K	80+	>50,000	120-277V	50/60Hz	45.9" X 12.6" X 3.5"

Ordering Guide

Example: VL-LH1671-165LED-50-MV-PM

VL-LH1671	MODEL	WATTS	COLOR TEMP	VOLTAGE	FINISH	OPTIONS		
VL-LH1671	105W-105LED	165W-165LED	220W-220LED	40-4000K	50-5000K	MV=120-277V	WH-WHITE	PK = PENDANT KIT OCC = OCCUPANCY SENSOR