



DATE	
PROJECT	
TYPE	
NOTE	
PREPARED BY	

**VL-PF70**

**Small LED Post Top Area Light**



The **VL-PF70** ensures powerful luminosity and provides security for any given location. It is constructed with robust die cast aluminum and given a clear prismatic lens to seal the LED array. In addition, the **VL-PF70** includes a polycarbonate prismatic outer conical lens. This fixture is designed to fit in various locations such as: residential areas, walkways, driveways and community parks. The **VL-PF70** offers competitive pricing and includes a 5 year warranty.

**FEATURES**

- Starting Temperature: -40°C ~ 50°C
- CRI: 80+
- Color temp: 4000K, 5000K
- Driver: Constant current, 120~277V
- Operating life: >50,000 hours
- 5 year warranty

**CONSTRUCTION**

- Die-cast aluminum body
- Black finish (standard)
- Clear prismatic array lens to seal LED array
- Polycarbonate prismatic outer conical lens

OPTIONS	
◦	SF- Single Fuse
◦	DF- Double Fuse
◦	SP- Surge Protection

MODEL #	INPUT POWER	LUMEN OUTPUT	COLOR TEMP (CCT)	CRI	RATED LIFE (L70)	INPUT VOLTAGE	INPUT FREQUENCY
VL-PF70-84LED	92.7W	5,854	4000K	80+	>50,000	120~277V	50/60Hz

# Ordering Guide

Example: VL-PF70-84LED-40-MV-BLK-SF

VL-PF70					
MODEL	WATTS	COLOR TEMP	VOLTAGE	FINISH	OPTIONS
VL-PF70	84W- <b>84LED</b>	40-4000K 50-5000K	<b>MV</b> —120~277V	<b>BLK</b> — BLACK	<b>SF</b> — SINGLE FUSE <b>DF</b> — DOUBLE FUSE <b>SP</b> — SURGE PROTECTION

# Dimensions

