



DATE	
PROJECT	
TYPE	
NOTE	
PREPARED BY	

VL-PF71

Small LED Post Top Area Light

The **VL-PF71** ensures powerful luminosity and provides security for any given location. It is constructed with robust die cast aluminum and given a clear prismatic lens to seal the LED array. In addition, the **VL-PF71** includes a polycarbonate prismatic outer conical lens. This fixture is designed to fit in various locations such as: residential areas, walkways, driveways and community parks. The **VL-PF71** offers competitive pricing and includes a 5 year warranty.



- OPTIONS**
- SF- Single Fuse
 - DF- Double Fuse
 - SP- Surge Protection

FEATURES

- Starting Temperature: -40°C ~ 50°C
- CRI: 80+
- Color temp: 4000K, 5000K
- Driver: Constant current, 120~277V
- Operating life: >50,000 hours
- 5 year warranty

CONSTRUCTION

- Die-cast aluminum body
- Black finish (standard)
- Clear prismatic array lens to seal LED array
- Polycarbonate prismatic outer conical lens

MODEL #	INPUT POWER	LUMEN OUTPUT	COLOR TEMP (CCT)	CRI	RATED LIFE (L70)	INPUT VOLTAGE	INPUT FREQUENCY
VL-PF71-84LED	92.7W	5,854	4000K	80+	>50,000	120~277V	50/60Hz

Ordering Guide

Example: VL-PF71-84LED-40-MV-BLK-SF

VL-PF71					
MODEL	WATTS	COLOR TEMP	VOLTAGE	FINISH	OPTIONS
VL-PF71	84W- 84LED	40-4000K 50-5000K	MV —120~277V	BLK —BLACK	SF — SINGLE FUSE DF — DOUBLE FUSE SP — SURGE PROTECTION

Dimensions

