



DATE	
PROJECT	
TYPE	
NOTE	
PREPARED BY	

VL-PFS80

Squared Large LED Post Top Area Light



The **VL-PFS80** ensures powerful luminosity and provides security for any given location. It is constructed with robust die cast aluminum and given a clear prismatic lens to seal the LED array. This area light is most competent in locations such as: walkways, pathways, driveways and community parks. The **VL-PFS80** offers competitive pricing and includes a 5 year warranty.

FEATURES

- Starting Temperature: -40°C ~ 50°C
- CRI: 80+
- Color temp: 5000K
- Driver: Constant current, 120~277V
- Operating life: >50,000 hours
- 5 year warranty



OPTIONS

- SF- Single Fuse
- DF- Double Fuse
- SP- Surge Protection

CONSTRUCTION

- Die-cast aluminum body
- Black finish (standard)
- Clear prismatic array lens to seal LED array

MODEL #	INPUT POWER	DELIVERED LUMENS	COLOR TEMP (CCT)	CRI	RATED LIFE (L70)	INPUT VOLTAGE	INPUT FREQUENCY
VL-PFS80-176LED	186W	18,883	5000K	80+	>50,000	120~277V	50/60Hz

Ordering Guide

Example: VL-PFS80-176LED-50-MV-BLK-SF

VL-PFS80

MODEL	WATTS	COLOR TEMP	VOLTAGE	FINISH	OPTIONS
VL-PFS80	176W-176LED	40-4000K	MV—120~277V	BLK—BLACK	SF— SINGLE FUSE
		50-5000K		BZ-BRONZE	DF— DOUBLE FUSE
				WH-WHITE	SP— SURGE PROTECTION
				GRY-GRAY	

Dimensions

