



DATE	
PROJECT	
TYPE	
NOTE	
PREPARED BY	

VL-SLR12

Globe with Sensor



The VL-SLR12 has a built-in photocell sensor that is beneficial for enhancing safety and security. It is ideal for locations such as residential exteriors, walkways, perimeters, school campuses, industrial/commercial spaces, and any other pedestrian travelled locations. The VL-SLR12 is also suitable for wet locations. Along with investing in a VL-SLR12 comes a 3 year warranty.

FEATURES

- Energy Savings: Over 66% compared to HID light sources
- Driver: Constant current, 120V, 50/60Hz
- Suitable for wet locations
- Operating life: >50,000 hours

CONSTRUCTION

- Acrylic lens
- Polycarbonate body

MODEL #	INPUT POWER	LUMEN OUTPUT	SCOTOPIC	COLOR TEMP (CCT)	CRI	RATED LIFE (L70)	INPUT VOLTAGE	INPUT FREQUENCY
VL-SLR12	12W	1,000	1,650	4000K	70+	>50,000	120V	50/60Hz

Ordering Guide

Example: VL-SLR12-12LED-40-120V-BZ

VL-SLR12

MODEL	WATTS	COLOR TEMP	VOLTAGE	FINISH
VL-SLR12	12W-12LED	40-4000K	MV=120V	BZ- BRONZE WH- WHITE

Dimensions

