



DATE	
PROJECT	
TYPE	
NOTE	
PREPARED BY	

VL-SFS

LED Architectural Floodlight



The VL-SFS is powerful, original, and durable. The VL-SFS provides savings to customers by adding the optional built-in photo sensor that automatically activates lighting at night and turns off lighting during daytime. It is ideal for locations such as parking areas, entrances, walkways, underpasses and roadways. The VL-SFS offers competitive pricing and includes a 5 year warranty.

FEATURES

- Starting Temperature: -40°C
- UL & CUL listed for wet locations
- IP 65
- Driver: Constant current, 120-277v
- Operating life: >50,000 hours

OPTIONS

- (JB) Junction box
- (PC) Photo control
- (PM) Pole mount
- (SF) Slip fitter
- (SB) Swivel bracket

CONSTRUCTION

- Solid construction die-cast aluminum body
- UV stabilized powder coat finish
- Powder coat bronze finish (standard)



SWIVEL BRACKET



JUNCTION BOX



SLIP FITTER



POLE MOUNT



PHOTO CONTROL

MODEL #	INPUT POWER	LUMEN OUTPUT	SCOTOPIC	COLOR TEMP (CCT)	CRI	RATED LIFE (L70)	INPUT VOLTAGE	INPUT FREQUENCY	HID EQUIVALENT
VL-TANGLE2-50LED	50W	3,846	10,662	4700K	70+	>50,000	120-277v	50/60Hz	150w-175w MH

Ordering Guide

Example: VL-SFS-50LED-47-MV-BZ-PC

MODEL	WATTS	COLOR TEMP	VOLTAGE	FINISH	OPTIONS
VL-SFS	50W-50LED	47-4700K	MV=120-277V	BZ- BRONZE	JB-JUNCTION BOX PC-PHOTO CONTROL PM-POLE MOUNT SB-WIVEL BRACKET SF-SLIP FITTER

Dimensions

