



DATE	
PROJECT	
TYPE	
NOTE	
PREPARED BY	

VL-TV3C3

LED Floodlight



** shown with slipfitter mounting

The **VL-TV3C3** provides powerful luminosity while keeping the LED's at a moderate temperature. It is constructed with robust die cast aluminum and given a tempered clear flat glass lens. This fixture is designed to fit in various locations such as: parking areas, entrances, walkways, underpasses and roadways. The **VL-TV3C3** offers competitive pricing and includes a 5 year warranty.

FEATURES

- Starting Temperature: -40°C ~ 50°C
- CRI: 70
- Color temp: 4100K
- UL listed for wet locations
- Driver: Constant current, 120~277V
- Operating life: >77,000 hours
- 5 year warranty

CONSTRUCTION

- Solid construction die-cast aluminum body
- Bronze finish (standard)
- Tempered clear flat glass lens

MODEL #	INPUT POWER	LUMEN OUTPUT	COLOR TEMP (CCT)	CRI	RATED LIFE (L70)	INPUT VOLTAGE	INPUT FREQUENCY	HID EQUIVALENT
VL-TV3C3-60LED	56W	6,509	4100K	70	>77,000	120~277V	50/60Hz	250w
VL-TV3C3-80LED	80W	8,221	4100K	70	>77,000	120~277V	50/60Hz	400w

Ordering Guide

Example: VL-TV3C3-60LED-41-MV-BZ-SP

VL-TV3C3					
MODEL	WATTS	COLOR TEMP	VOLTAGE	FINISH	OPTIONS
VL-TV3C3	60W-60LED 80W-80LED	41-4100K	MV—120~277V	BZ- BRONZE	SP—SURGE PROTECTION

Dimensions

