



DATE	
PROJECT	
TYPE	
NOTE	
PREPARED BY	

**VL-TANGLE2**

**LED Architectural Floodlight**



The energy efficient LED light fixture, **VL-TANGLE2** provides savings to customers by adding the optional built-in photo sensor that automatically activates lighting at night and turns off lighting during daytime. It is ideal for locations such as parking areas, entrances, walkways, underpasses and roadways. The multifunctional **VL-TANGLE2** can be installed with a swivel bracket, slip-fitter, or a pole mount. The **VL-TANGLE2** offers competitive pricing and includes a 5 year warranty.

**FEATURES**

- Starting Temperature: -40°C
- UL & CUL listed for wet locations
- Driver: Constant current, 120-277v
- Operating life: >50,000 hours
- 5 year warranty

**OPTIONS**

- (PC) Photo control
- (PM) Pole mount
- (SB) Swivel bracket
- (SF) Slip fitter

**CONSTRUCTION**

- Solid construction die-cast aluminum body
- UV stabilized powder coat finish
- Powder coat bronze finish (standard)



POLE MOUNT



SLIP FITTER



SWIVEL BRACKET

MODEL #	INPUT POWER	LUMEN OUTPUT	SCOTOPIC	COLOR TEMP (CCT)	CRI	RATED LIFE (L70)	INPUT VOLTAGE	INPUT FREQUENCY	HID EQUIVALENT
VL-TANGLE2-21LED	21W	1,753	2,893	5000K	70+	>50,000	120-277v	50/60Hz	100w MH
VL-TANGLE2-53LED	53W	5,469	9,024	5000K	70+	>50,000	120-277v	50/60Hz	250w MH

# Ordering Guide

Example: VL-TANGLE2-21LED-50-MV-BZ-PC

VL-TANGLE2					
MODEL	WATTS	COLOR TEMP	VOLTAGE	FINISH	OPTIONS
VL-TANGLE2	21W-21LED 53W-53LED	50-5000K	MV=120-277V	BZ- BRONZE	PC-PHOTO CONTROL PM-POLE MOUNT SF-SLIP FITTER SB-WIVEL BRACKET

# Dimensions

